


Technical Data Sheet

Last data update

3/15/2016

9010
novantadieci®




Req. space behind the plasterboard

60mm




hole on the plasterboard

125x125mm




External measures

120x120mm




Measures of the light output

50x70mm



Height without electrical part

45mm



Height including the electrical part

45mm

Notes on measures

General notes

PASSO

4112-4000

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 2W / 24Vdc / 210lm / 4000°K / CRI85

Model

| | |
|----------------|--------------------|
| Code | 4112 |
| Product family | PASSO |
| Type | Recessed Spotlight |

Material/Surface finish

| | |
|----------------|----------|
| Code | 004 |
| Material | CRISTALY |
| Surface finish | CRISTALY |

Electrical part

| | |
|--------------------------|------------------------|
| Code | 4000 |
| Type | LED |
| Power | 2W |
| Tension | 24Vdc |
| Light Output | 210lm |
| Colour Temperature | 4000°K |
| CRI | 85 |
| Light Output of the lamp | 128,1lm |
| Dimmable | SI |
| Power Supply | by Remote Power Supply |
| Connection | 2 PVC cables |
| Cover | |

General Data

| | |
|-----------------------|--------------------|
| Protection Index | IP20 |
| Isolation Class | III |
| Weight [Kg] | 0,55 |
| Country of production | MADE IN ITALY |
| Mounting instruction | 025.392_9010_REV05 |

Installation

| | |
|------------------|-----------------|
| Multisize system | SI |
| Position | Wall pathmarker |


Packaging

| | |
|----------------------|-------------------|
| Type | White die-cut Box |
| Measures AxBxH | 165x165x116mm |
| Gross Weight [Kg] | 0,6147 |
| Master carton | NO |
| Quantity of articles | |
| Measures AxBxH | |

Technical Data Sheet

4112-4000

Fotometric Data




| | |
|---------------------------|--------|
| <i>Electrical part</i> | 4000_C |
| <i>Power</i> | 2W |
| <i>Light Output</i> | 210lm |
| <i>Colour Temperature</i> | 4000°K |
| <i>CRI</i> | 85 |

| | | |
|--------------------|------|--------|
| <i>Illuminance</i> | 0.3m | 797lux |
| | 0.5m | 287lux |
| | 1m | 72lux |

| | |
|---------------------------------|---------|
| <i>Lamp Light Output</i> | 61% |
| <i>Light Output of the lamp</i> | 128,1lm |
| <i>Beam Angle</i> | 53° |
| <i>Beam Inclination</i> | 42° |


Accessories

Housing Box for Brickwork




| | |
|--------------------------------|--------------|
| <i>Code</i> | 023.421 |
| <i>Measures</i> | 125X125X60mm |
| <i>Measures of the hole on</i> | 155X155X70mm |

Standard Power Supply



| | |
|-----------------|-------------|
| <i>Code</i> | 026.258 |
| <i>Measures</i> | 130x42x23mm |
| <i>Power</i> | 12W |
| <i>Input</i> | 220-240V~W |
| <i>Output</i> | 24Vdc |




| | |
|-----------------|-------------|
| <i>Code</i> | 026.259 |
| <i>Measures</i> | 167x45x30mm |
| <i>Power</i> | 36W |
| <i>Input</i> | 220-240V~W |
| <i>Output</i> | 24Vdc |




| | |
|-----------------|-------------|
| <i>Code</i> | 026.260 |
| <i>Measures</i> | 157x54x36mm |
| <i>Power</i> | 60W |
| <i>Input</i> | 220-240V~W |
| <i>Output</i> | 24Vdc |

Dimmable Power Supply



| | |
|-----------------|-----------------|
| <i>Code</i> | 026.219 |
| <i>Measures</i> | 155x51x26mm |
| <i>Power</i> | 21,6W |
| <i>Input</i> | 220-240V~W |
| <i>Output</i> | 24Vdc |
| <i>Dimmable</i> | PUSH/0-10V/DALI |



| | |
|-----------------|-------------|
| <i>Code</i> | 026.209 |
| <i>Measures</i> | 125x82x29mm |
| <i>Power</i> | 60W |
| <i>Input</i> | 220-240 V~W |
| <i>Output</i> | 24Vdc |
| <i>Dimmable</i> | PUSH/1-10V |

4112-4000

Accessories

Other Accessories



| | |
|--------------------|---------------|
| <i>Code</i> | 099.142 |
| <i>Description</i> | Emergency Kit |
| <i>Notes</i> | |