


Technical Data Sheet

Last data update


3/15/2016

9010
novantadieci®




Req. space behind the plasterboard

50mm



hole on the plasterboard

305x115mm




External measures

300x110mm




Measures of the light output

250x40mm



Height without electrical part

40mm



Height including the electrical part

40mm

Notes on measures

General notes

PASSO

4156-4004

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 5.5W / 24Vdc / 530lm / 4000°K / CRI85

Model

Code	4156
Product family	PASSO
Type	Recessed Spotlight

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	4004
Type	LED
Power	5.5W
Tension	24Vdc
Light Output	530lm
Colour Temperature	4000°K
CRI	85
Light Output of the lamp	439,9lm
Dimmable	SI
Power Supply	by Remote Power Supply
Connection	2 PVC cables
Cover	Transparent Polycarbonate

General Data

Protection Index	IP20
Isolation Class	III
Weight [Kg]	1,2
Country of production	MADE IN ITALY
Mounting instruction	025.333_9010_REV03

Installation

Multisize system	NO
Position	Wall/Ceiling lighting


Packaging

Type	White american Box
Measures AxBxH	339x176x81mm
Gross Weight [Kg]	1,2991
Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

4156-4004

Fotometric Data




<i>Electrical part</i>	4004_5,5
<i>Power</i>	5.5W
<i>Light Output</i>	530lm
<i>Colour Temperature</i>	4000°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	83%
<i>Light Output of the lamp</i>	439,9lm
<i>Beam Angle</i>	63°
<i>Beam Inclination</i>	50°

<i>Illuminance</i>	0.3m	2268lux
	0.5m	816lux
	1m	204lux


Accessories

Housing Box for Brickwork




<i>Code</i>	023.422
<i>Measures</i>	305X115X50mm
<i>Measures of the hole on</i>	335X145X60mm

Standard Power Supply




<i>Code</i>	026.258
<i>Measures</i>	130x42x23mm
<i>Power</i>	12W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.259
<i>Measures</i>	167x45x30mm
<i>Power</i>	36W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc



<i>Code</i>	026.260
<i>Measures</i>	157x54x36mm
<i>Power</i>	60W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.261
<i>Measures</i>	219x63x35.5mm
<i>Power</i>	150W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.262
<i>Measures</i>	244x71x35.5mm
<i>Power</i>	240W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc

Accessories


Dimmable Power Supply




Code 026.219
 Measures 155x51x26mm
 Power 21,6W
 Input 220-240V~W
 Output 24Vdc
 Dimmable PUSH/0-10V/DALI



Code 026.209
 Measures 125x82x29mm
 Power 60W
 Input 220-240 V~W
 Output 24Vdc
 Dimmable PUSH/1-10V




Code 026.190+026.261
 Measures 156x52x24mm
 Power 150W
 Input 180-295V~W
 Output 24Vdc
 Dimmable PUSH/0-10V/DALI



Code 026.190+026.262
 Measures 156x52x24mm
 Power 240W
 Input 180-295V~W
 Output 24Vdc
 Dimmable PUSH/0-10V/DALI

Other Accessories



Code 099.142
 Description Emergency Kit
 Notes