

Technical Data Sheet

Last data update


3/15/2016

9010
novantadieci®



Req. space behind the plasterboard

70mm




hole on the plasterboard

480x480mm



External measures

475x475mm



Measures of the light output

325x355mm



Height without electrical part

65mm



Height including the electrical part

65mm

Notes on measures

General notes

INCASSO A PLAFONE

8917-2705

Recessed lighting / CRISTALY

Surface finish : CRISTALY

LED 28.5W / 24Vdc

Model

Code	8917
Product family	INCASSO A PLAFONE
Type	Recessed lighting

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	2705
Type	LED
Power	28.5W
Tension	24Vdc
Light Output	2400lm
Colour Temperature	2700°K
CRI	85
Light Output of the lamp	480lm
Dimmable	SI
Power Supply	by Remote Power Supply
Connection	Screw Terminal
Cover	Satin Polycarbonate

General Data

Protection Index	IP20
Isolation Class	III
Weight [Kg]	6,2
Country of production	MADE IN ITALY
Mounting instruction	025.378_9010_REV04

Installation

Multisize system	SI
Position	Ceiling


Packaging

Type	White american Box
Measures AxBxH	610x610x240mm
Gross Weight [Kg]	8,0307
Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

8917-2705

Fotometric Data




<i>Electrical part</i>	2705_28,5
<i>Power</i>	28.5W
<i>Light Output</i>	2400lm
<i>Colour Temperature</i>	2700°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	20%
<i>Light Output of the lamp</i>	480lm
<i>Beam Angle</i>	45°
<i>Beam Inclination</i>	0°


<i>Illuminance</i>	1m	482lux
	2m	121lux
	3m	54lux
	4m	30lux
	5m	19lux

Accessories


Standard Power Supply




<i>Code</i>	026.259
<i>Measures</i>	167x45x30mm
<i>Power</i>	36W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc



<i>Code</i>	026.260
<i>Measures</i>	157x54x36mm
<i>Power</i>	60W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.261
<i>Measures</i>	219x63x35.5mm
<i>Power</i>	150W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.262
<i>Measures</i>	244x71x35.5mm
<i>Power</i>	240W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc


Dimmable Power Supply



<i>Code</i>	026.209
<i>Measures</i>	125x82x29mm
<i>Power</i>	60W
<i>Input</i>	220-240 V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/1-10V




<i>Code</i>	026.190+026.261
<i>Measures</i>	156x52x24mm
<i>Power</i>	150W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/0-10V/DALI



<i>Code</i>	026.190+026.262
<i>Measures</i>	156x52x24mm
<i>Power</i>	240W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/0-10V/DALI

Other Accessories



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	