

Technical Data Sheet

Last data update


3/15/2016

9010
novantadieci®



Req. space behind the plasterboard

70mm




hole on the plasterboard

480x480mm



External measures

475x475mm



Measures of the light output

325x355mm



Height without electrical part

65mm



Height including the electrical part

65mm

Notes on measures

General notes

INCASSO A PLAFONE

8917-4005

Recessed lighting / CRISTALY

Surface finish : CRISTALY

LED 28.5W / 24Vdc

Model

Code	8917
Product family	INCASSO A PLAFONE
Type	Recessed lighting

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	4005
Type	LED
Power	28.5W
Tension	24Vdc
Light Output	2700lm
Colour Temperature	4000°K
CRI	85
Light Output of the lamp	540lm
Dimmable	SI
Power Supply	by Remote Power Supply
Connection	Screw Terminal
Cover	Satin Polycarbonate

General Data

Protection Index	IP20
Isolation Class	III
Weight [Kg]	6,2
Country of production	MADE IN ITALY
Mounting instruction	025.378_9010_REV04

Installation

Multisize system	SI
Position	Ceiling

Packaging


Type	White american Box
Measures AxBxH	610x610x240mm
Gross Weight [Kg]	8,0307
Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

9010
novantadieci®

8917-4005

Fotometric Data




<i>Electrical part</i>	4005_28,5
<i>Power</i>	28.5W
<i>Light Output</i>	2700lm
<i>Colour Temperature</i>	4000°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	20%
<i>Light Output of the lamp</i>	540lm
<i>Beam Angle</i>	45°
<i>Beam Inclination</i>	0°


<i>Illuminance</i>	1m	543lux
	2m	136lux
	3m	60lux
	4m	34lux
	5m	22lux

Accessories


Standard Power Supply




<i>Code</i>	026.259
<i>Measures</i>	167x45x30mm
<i>Power</i>	36W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc



<i>Code</i>	026.260
<i>Measures</i>	157x54x36mm
<i>Power</i>	60W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.261
<i>Measures</i>	219x63x35.5mm
<i>Power</i>	150W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.262
<i>Measures</i>	244x71x35.5mm
<i>Power</i>	240W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc


Dimmable Power Supply



<i>Code</i>	026.209
<i>Measures</i>	125x82x29mm
<i>Power</i>	60W
<i>Input</i>	220-240 V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/1-10V




<i>Code</i>	026.190+026.261
<i>Measures</i>	156x52x24mm
<i>Power</i>	150W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/0-10V/DALI



<i>Code</i>	026.190+026.262
<i>Measures</i>	156x52x24mm
<i>Power</i>	240W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/0-10V/DALI

Other Accessories



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	