


# Technical Data Sheet

Last data update


3/15/2016

9010  
novantadieci®




Req. space behind the plasterboard

30mm




hole on the plasterboard

37x3025 ±10mm




External measures

90x3020 ±10mm



Measures of the light output

36x3020 ±10mm



Height without electrical part

35mm

## Notes on measures

## General notes

## PROFILO

P001D-00

Recessed Profile / ALUMITE

Surface finish : ALUMITE

Senza parte elettrica - Without electrical part - / -

## Model

Code	P001D
Product family	PROFILO
Type	Recessed Profile

## Material/Surface finish

Code	006
Material	ALUMITE
Surface finish	ALUMITE

## Electrical part

Code	00
Type	Senza parte elettrica - Without electrical part

## General Data

Protection Index	
Isolation Class	
Weight [Kg]	2,4
Cover	Opaline Methacrylate
Country of production	MADE IN ITALY
Mounting instruction	025.452_9010_REV02

## Installation

Multisize system	NO
Position	Wall/Ceiling lighting


## Packaging

Type	Brown carton tube
Measures AxBxH	90x90x3100mm
Gross Weight [Kg]	2,9148
Master carton	NO
Quantity of articles	
Measures AxBxH	

## Technical Data Sheet

P001D-00

### Fotometric Data



<i>Electrical part</i>	021.792.300
<i>Power</i>	78W
<i>Light Output</i>	9000lm
<i>Colour Temperature</i>	3000°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	58%
<i>Light Output of the lamp</i>	5220lm
<i>Beam Angle</i>	86°
<i>Beam Inclination</i>	0°

<i>Illuminance</i>	1m	2302lux
	2m	576lux
	3m	256lux
	4m	144lux
	5m	92lux

### Accessories

#### LED strip



<i>Code</i>	021.790
<i>Power</i>	15W/m
<i>Tension</i>	24Vdc
<i>Flux</i>	1400lm/m
<i>Colour Temperature</i>	3000°K
<i>CRI</i>	85
<i>led/m</i>	120




<i>Code</i>	021.791
<i>Power</i>	18W/m
<i>Tension</i>	24Vdc
<i>Flux</i>	2000lm/m
<i>Colour Temperature</i>	3000°K
<i>CRI</i>	85
<i>led/m</i>	224




<i>Code</i>	021.792
<i>Power</i>	26W/m
<i>Tension</i>	24Vdc
<i>Flux</i>	3000lm/m
<i>Colour Temperature</i>	3000°K
<i>CRI</i>	85
<i>led/m</i>	224


#### Other Accessories




<i>Code</i>	023.700
<i>Description</i>	Linear connection
<i>Notes</i>	



<i>Code</i>	023.701
<i>Description</i>	L connection
<i>Notes</i>	




<i>Code</i>	023.702
<i>Description</i>	T connection
<i>Notes</i>	



<i>Code</i>	023.703
<i>Description</i>	X connection
<i>Notes</i>	




<i>Code</i>	023.704
<i>Description</i>	Wall/Ceiling connection
<i>Notes</i>	



<i>Code</i>	P001.KIT01
<i>Description</i>	Couple of end caps
<i>Notes</i>	



<i>Code</i>	029.009.300
<i>Description</i>	Replacement opal cover
<i>Notes</i>	L 3000mm



<i>Code</i>	TGA
<i>Description</i>	Cut to size
<i>Notes</i>	