Coral Seaurchin

ref. **COAU04**

Pendant lamp
Lámpara colgante

Click here to download:
3D/2D, pictures, photometric curves
and assembly instructions

Clica aquí para descargar:
3D/2D, fotografías, curvas fotométricas
e instrucciones de montaje

SIMETECH® by arturo alvarez

INTERIOR DESIGN BEST OF YEAR 2014
Innovative translucent shading
lighting solution

Coral Collection

COAU04 | COAU04G | COREO4 | COGAO4 | COCYO4 | COSEO4 | CO04-3 | CO04-5 | CO04-10

MATERIAL FINISHES
MATERIALES Y ACABADOS

LAMPSHADE
TULIPA

SIMETECH® by arturo alvarez

One colour to choose
Un color a elegir



Stainless steel
Acero inoxidable

CANOPY AND CABLE
FLORÓN Y CABLE

Steel gloss nickel-plated
Acero niquel-satinado

Black or transparent cable
Cable negro o transparente

LIGHT SOURCE
FUENTE DE LUZ

230V - 50Hz

- E27 - Max. 1x23 W
- E27 LED - Max. 1x11 W
- E27 ECO - Max. 1x77 W
- E27 LED - Max. 1x12 W
- E27 - Max. 1x100 W

120V - 60Hz

- E26 Med. - Max. 1x100 W
- E26 Med. - Max. 1x42 W

ENERGY EFFICIENCY
EFICIENCIA ENERGÉTICA

from A+ to E
desde A+ a E

OTHER TECHNICAL DATA
OTROS DATOS TÉCNICOS

PACKAGING
EMBALAJE

44x43x31cm | 17,3x 16,9x 12,2in
2,4kg | 5,4lb

ELECTRICAL FEATURES
CARACTERÍSTICAS ELÉCTRICAS

CERTIFICATIONS
CERTIFICACIONES

arturo alvarez
emotional light

Handmade in Spain

www.arturo-alvarez.com

Coral Seaurchin

LED

ref. **COAU04-LD** LED / DIMMABLE

Pendant lamp
Lámpara colgante

SIMETECH® by arturo alvarez

INTERIOR DESIGN BEST OF YEAR 2014
Innovative translucent shading lighting solution

Coral Collection

COAU04 | COAU04G | CORE04 | COGA04 | COCY04 | COSE04 | CO04-3 | CO04-5 | CO04-10

MATERIAL FINISHES
MATERIALES Y ACABADOS

LAMPSHADE
TULIPA

SIMETECH® by arturo alvarez

One colour to choose
Un color a elegir



Stainless steel
Acero inoxidable

CANOPY AND CABLE
FLORÓN Y CABLE

Steel gloss nickel-plated
Acero niquel-satinado

Black or transparent cable
Cable negro o transparente

LIGHT SOURCE
FUENTE DE LUZ

230V - 50Hz

24,9W 3000K 2353lm built-in
upon request 2700K 2223lm

Dimming system: DALI / Switch DIM
upon request PHASE CUT

120V - 60Hz

16,6W 3000K 1530lm built-in
upon request 2700K 1449lm

Dimming system: 0-10 V

ENERGY EFFICIENCY
EFICIENCIA ENERGÉTICA

from A++ to A
desde A++ a A

OTHER TECHNICAL DATA
OTROS DATOS TÉCNICOS

PACKAGING
EMBALAJE

44x43x31cm | 17,3x 16,9x 12,2in
2,4kg | 5,4lb

ELECTRICAL FEATURES
CARACTERÍSTICAS ELÉCTRICAS

CERTIFICATIONS
CERTIFICACIONES