

Coral Sea

ref. **COSE04**

Pendant lamp

Lámpara colgante

[Click here to download:](#)

3D/2D, pictures, photometric curves
and assembly instructions

[Clica aquí para descargar:](#)

3D/2D, fotografías, curvas fotométricas
e instrucciones de montaje

SIMETECH® by arturo alvarez

**BEST
OF
YEAR 2014**

Innovative translucent shading
lighting solution

25cm | 9,8in

Ø8cm | 3,2in

150cm | 59,1in

Ø35cm | 13,8in

Coral Collection



COAU04



COAU04G



CORE04



COGA04



COCY04



COSE04



C004-3



C004-5



C004-10


MATERIAL FINISHES MATERIALES Y ACABADOS

LAMPSHADE TULIPA

SIMETECH® by arturo alvarez

One colour to choose

Un color a elegir



Stainless steel
Acero inoxidable

CANOPY AND CABLE FLORÓN Y CABLE

Steel gloss nickel-plated
Acero niquel-satinado

Black or transparent cable
Cable negro o transparente

LIGHT SOURCE FUENTE DE LUZ

230V - 50Hz



E27 - Max. 1x23 W



E27 LED - Max. 1x11 W



E27 ECO - Max. 1x77 W



E27 LED - Max. 1x12 W



E27 - Max. 1x100 W

120V - 60Hz



E26 Med. - Max. 1x100 W



E26 Med. - Max. 1x42 W

ENERGY EFFICIENCY EFICIENCIA ENERGÉTICA

from A+ to E
desde A+ a E

OTHER TECHNICAL DATA OTROS DATOS TÉCNICOS

PACKAGING EMBALAJE

36x36x30cm | 14,2x 14,2x 11,8in

1,7kg | 3,7lb

ELECTRICAL FEATURES CARACTERÍSTICAS ELÉCTRICAS



CERTIFICATIONS CERTIFICACIONES



arturo alvarez

emotional light

Handmade in Spain

www.arturo-alvarez.com

Coral Sea

LED

ref. COSE04-LD

LED / DIMMABLE

Pendant lamp

Lámpara colgante

SIMETECH® by arturo alvarez

INTERIOR
DESIGN
**BEST
OF
YEAR 2014**

Innovative translucent shading
lighting solution

Ø14,2cm | 5,6in

150cm | 59,1in

25cm | 9,8in

Ø35cm | 13,8in

Coral Collection



MATERIAL FINISHES MATERIALES Y ACABADOS


LAMP SHADE

TULIPA

SIMETECH® by arturo alvarez

One colour to choose

Un color a elegir



Stainless steel
Acero inoxidable

CANOPY AND CABLE

FLORÓN Y CABLE

Steel gloss nickel-plated
Acero níquel-satinado

Black or transparent cable
Cable negro o transparente

LIGHT SOURCE FUENTE DE LUZ

230V - 50Hz

⊙ 24,9W 3000K 2353lm built-in
upon request 2700K 2223lm

Dimming system: DALI / Switch DIM
upon request PHASE CUT

120V - 60Hz

⊙ 16,6W 3000K 1530lm built-in
upon request 2700K 1449lm

Dimming system: 0-10 V

ENERGY EFFICIENCY

EFICIENCIA ENERGÉTICA

from A++ to A
desde A++ a A

OTHER TECHNICAL DATA OTROS DATOS TÉCNICOS

PACKAGING

EMBALAJE

36x36x30cm | 14,2x 14,2x 11,8in
1,7kg | 3,7lb

ELECTRICAL FEATURES

CARACTERÍSTICAS ELÉCTRICAS



CERTIFICATIONS

CERTIFICACIONES

