

ANDES LED 2 ADJUSTABLE DOWNLIGHT

TRUE COLOUR CRI 98 | IP54

DLD/ANDE2-R-A

DLD
ARCHITECTURAL




DETAILS

Type	Adjustable 24°
IP Rating	IP54
IP Zone	Zone 2
Class	I
Standards	CE
Fire Rated	60+ minutes
Material	Aluminium
Cable	2 Core 0.5mm ²
Cable Length	400mm
Warranty	5 Years


KEY POINTS

- True Colour CRI 98, amazingly high level of colour rendering
- R9 95, reds are redder than ever
- Simple access to the light engine for easy maintenance
- Dim to dark with our range of fully tested drivers

DIMENSIONS



Light Engine:	Ø64mm, H.89mm
Aperture:	Ø35.5mm
Frame:	180mm x 90mm H.35.2mm
Total Height:	105mm
Cutout:	165mm x 80mm



TRUE COLOUR 98 CRI

ANDES LED 2 ADJUSTABLE DOWNLIGHT

TRUE COLOUR CRI 98 | IP54

DLD/ANDE2-R-A

DLD
ARCHITECTURAL

PRODUCT CODE CONSTRUCTION

PRODUCT CODE PREFIX	FINISH	BAFFLE	LIGHT TEMP. CCT	BEAM ANGLE	DRIVER
DLD/ANDE2-R-A	W	B	27K	24D	010
<i>APPLICATION</i> P Plaster In R Recessed	<i>VERSION</i> A Adj. F Fixed	W White B Black G Gold	27K 2700K 30K 3000K 40K 4000K	15D 15° 24D 24° 36D 36°	No driver MD TRIAC dim. 010 0-10V dim. D DALI dim.

SPECIFICATION

BEAM ANGLE

Delivered lumens*
*(Tc 85°C, +/-7%)
Efficacy Lm/W

15°

available
on
request

24°

available
on
request

36°

955 lm
78 lm/W

CCT

3000K

Binning SDCM (Hot)
CRI
R9
TM30 Rf Rg

2
98
95
Rf 95 Rg 95

LED Type
LED Lifetime (Ave.)

Luminus Gen. 6 CXM-6 COB LED
50,000 hrs

POWER

Wattage
Voltage
Current

2 x 12W
220-240V
2 x 350mA

DRIVER

Supported Protocols
Dim to Dark
Distance from Luminaire
Wiring
Emergency

Mains Dim / TRIAC / 0-10V / DALI / Bluetooth
0.1% Lux
20m maximum
Series
Emergency packs available

 **01189 889414**

 **sales@darklightdesign.com**

 **darklightdesign.com**

Darklight Design
Unit 10 Brookside Business Centre
Church Road
Swallowfield
Reading
Berkshire
RG7 1TH