# LODES

# Nautilus, *design by* Andrea Tosetto, 2017

Ceiling

Strong design and leading—edge technology come together in this family of lamps characterised by a convex lens that projects the LED light wherever its needed or most preferred, for a truly efficient and personalised result. Versatile and dynamic, either on the wall, ceiling or suspended in a variety of versions and finishes, Nautilus lamps satisfy a full range of lighting needs, whether functional or purely decorative, in both residential and professional contexts.



Nautilus Ceiling		Light source		Frame: Aluminium			Diffuse	r: Aluminium	Code
		LED • 3000 K		( ) Chrome			_		165016
		• 1 × 15W   12 • 220-240V	1275 lm	Matte Black 9005			_		165015
		<ul><li>CRI 90</li><li>MacAdam</li></ul>	3-Step	Matte White 9010					165014
		LED and driver included	included	Matte Ch	165034				
		LED • 2700 K • 1 × 15W   1200 lm • 220-240V	Matte Wi	hite 901	0	_		165011	
			Chrome —					165013	
		<ul><li>CRI 90</li><li>MacAdam 3-Step</li><li>LED and driver included</li></ul>		Matte Bla	ack 900	5	_		165012
				Matte Champagne			_		165033
				_					
Net weight: 1.10 kg	Gross weight: 1.59 kg	Parcels: N°1	Volume: 0.008 m³		C€	IP40	EAC	Energy Saving (	Dim Triac 💇

Nautilus Spot		Light source		Frame: Metal				Diffuser: Aluminium		Code
		LED • 2700 K		Matte White 9010			10	_		165035
		• 1 × 10W  800 lm • 220-240V	Matte Black 9005			_		165036		
		<ul><li>CRI 90</li><li>MacAdam 3-Step</li></ul>		( ) Chrome				_		165037
		LED and driver included		Matte Champagne			ne	_		165038
		LED • 3000 K	Matte White 9010			10			165039	
		• 1 x 10W   850 lm • 220-240V • CRI 90 • MacAdam 3-Step	850 lm	Matte Black 9005				165040		
			( ) Chrome						165043	
		LED and driver	r included	Matte Champagne			ne	_		165044
				_						
Net weight: 0.56 kg	Gross weight: 0.94 kg	Parcels: N°1	Volume: 0.005 m³			C€	EAC	IP20	Energy Saving (\$	Dim Triac 💩

# Polar diagram

# C0-C180 / C90-C270 cd/1000lm

# Nautilus Ceiling

- LED
   2700 K
   1 × 10W |800 lm
- 220-240V
- CRI 90
- MacAdam 3-Step


LED and driver included

- LED 3000 K
- 1 × 10W | 850 lm
- 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

Polar diagram

Nautilus Spot



## LED

- 2700 K 1 × 10W |800 lm 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

- LED
   3000 K
   1 × 10W | 850 lm
- 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

# Other applications of Nautilus





Wall

Suspension