

Cardanic Spot



Glare-free to due shielded lens technology

Low weight and compact modern design

Low maintenance costs with lens technology



2 luminaire head positions to reach upper wall segments

Fast installation with spring fixation



Installation: Optic:	Ceiling recessed Lens 12°/24°/38°/55°
Driver: Materials:	FIX, DALI Luminaire head - Aluminium Housing - Metal sheet Linse - Polycarbonate
Colors:	Black RAL 9005, White RAL 9003
Weight:	1.2 kg
Lifetime:	L80B10 50.000 Hours
Ambient temperature:	0 / +35° C

Dimensions:



Ceiling cutout: 165 x 165 mm

Code	Power	CRI	CCT	Lumen
CS	16 W	> 90	2700 K	1300 lm
CS	16 W	> 90	3000 K	1400 lm
CS	16 W	> 95	3200 K	1300 lm
CS	16 W	> 90	4000 K	1600 lm
CS	28 W	> 90	2700 K	2200 lm
CS	28 W	> 90	3000 K	2400 lm
CS	28 W	> 95	3200 K	2200 lm
CS	28 W	> 90	4000 K	2700 lm

Tolerance of light output and color temperature: +/- 10%

Order example:

CS	-	Power	-	CRI / CCT	-	Beam	-	Color	-	Driver	-	OPTION
CS	-	16	-	930	-	55	-	BL	-	DALI	-	XYZ

We reserve the right to change product specifications without prior information