

FLEX TRACK

The FLEX TRACK SYSTEM is the dedicated on-track system on which the spots are fixed through a magnetic / mechanic fixing system.

Black anodized aluminium body. Integrated aluminium joint allow fixation and adjustment of the spot orientation. No cables are visible.

CRI 90.



FIXED OPTIC | 3000K - 15°

LAMPING

Source	LED spot
Total power	5W
Emission	Direct 15°
Tension	24VDC
Color temperature	3000K
Initial luminaire efficacy	53lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	20
Dimensions	ø3,3x16,6x7cm
Materials	Anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	20°
Net lamp weight	0,4 kg

Codes

MFLE5101N21WAN

Structure

black

PACKAGE


Package 01

Dimension: 20x10x10 cm / Gross weight: 0,45 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



TRACK



FIXED OPTIC | 3000K - 25°

LAMPING

Source	LED spot
Total power	5W
Emission	Direct 25°
Tension	24VDC
Color temperature	3000K
Luminous flux	265lm
Initial luminaire efficacy	53lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	20
Dimensions	ø3,3x16,6x7cm
Materials	Anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	20°
Net lamp weight	0,4 kg

Codes

MFLE5101421WAN

Structure

black

PACKAGE


Package 01

Dimension: 20x10x10 cm / Gross weight: 0,45 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



TRACK



FIXED OPTIC | 4000K - 15°

LAMPING

Source	LED spot
Total power	5W
Emission	Direct 15°
Tension	24VDC
Color temperature	4000K
Initial luminaire efficacy	53lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	20
Dimensions	ø3,3x16,6x7cm
Materials	Anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	20°
Net lamp weight	0,4 kg

Codes

MFLE5101N21NAN

Structure

black

PACKAGE


Package 01

Dimension: 20x10x10 cm / Gross weight: 0,45 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



TRACK



FIXED OPTIC | 4000K - 25°

LAMPING

Source	LED spot
Total power	5W
Emission	Direct 25°
Tension	24VDC
Color temperature	4000K
Initial luminaire efficacy	16lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	20
Dimensions	ø3,3x16,6x7cm
Materials	Anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	20°
Net lamp weight	0,4 kg

Codes

MFLE5101421NAN

Structure

black

PACKAGE


Package 01

Dimension: 20x10x10 cm / Gross weight: 0,45 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



TRACK



ZOOM OPTIC | 3000K

LAMPING

Source	LED spot
Total power	5W
Emission	Direct adjustable 7°-45°
Tension	24VDC
Color temperature	3000K
Initial luminaire efficacy	16lm/W
Typ cri	90
Energy class	A+
Ip class	20
Dimensions	ø3,3x16,6x9,6cm
Materials	Anodized aluminum
Net lamp weight	0,4 kg

Codes

MFLE5101921WAN

Structure

black

PACKAGE


Package 01

Dimension: 20x10x10 cm / Gross weight: 0,45 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



TRACK



ZOOM OPTIC | 4000K

LAMPING

Source	LED spot
Total power	5W
Emission	Direct adjustable 7°-45°
Tension	24VDC
Color temperature	4000K
Typ cri	90
Energy class	A+
Ip class	20
Dimensions	ø3,3x16,6x9,6cm
Materials	Anodized aluminum
Net lamp weight	0,4 kg

Codes

MFLE5101921NAN

Structure

black

PACKAGE


Package 01

Dimension: 100x5x5 cm / Gross weight: 0,75 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



TRACK



TRACK 1M CEILING-PENDANT

LAMPING

Energy class

A+

Materials

Anodized aluminum

Accessories

Drivers 24VDC + DALI interface, | Flex track accessories,
End caps, feeding, joint

Net lamp weight

0,7 kg

Codes

MFLEBKBINARIO1E

Structure

black

PACKAGE


Package 01

Dimension: 200x5x5 cm / Gross weight: 0,75 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



TRACK



TRACK 2M CEILING-PENDANT

LAMPING

Initial chromaticity	SDCM < 2
Energy class	A+
Materials	Anodized aluminum
Ambient temperature range	0° / 35°
Performance ambient temperature	25°
Mechanical impact protection code	IK02
Customization options	CRI, Temperature colour, Casambi
Accessories	Drivers 24VDC + DALI interface, Flex track accessories, End caps, feeding, joint
Net lamp weight	0,7 kg

Codes

MFLEBKBINARIO2E

Structure

black


PACKAGE

Package 01 Dimension: 300x5x5 cm / Gross weight: 0,75 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



TRACK



TRACK 3M CEILING-PENDANT

LAMPING

Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 2
Energy class	A+
Materials	Anodized aluminum
Ambient temperature range	0° / 35°
Performance ambient temperature	25°
Mechanical impact protection code	IK02
Customization options	CRI, Temperature colour, Casambi
Accessories	Drivers 24VDC + DALI interface, Flex track accessories, End caps, feeding, joint
Net lamp weight	0,7 kg

Codes

MFLEBKBINARIO3E

Structure

black

PACKAGE


Package 01

Dimension: 30x28x5 cm / Gross weight: 1,8 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



TRACK

