ACCENT 24V





LANDSCAPE LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

61/8"

PRODUCT DESCRIPTION

Landscape accent luminaire. One fixture replaces all older halogen landscape accent lights

FEATURES

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- MLV dimmable with remote MLV dimmers

ORDERING NUMBER

		Color Temp		Finish	
5011	Accent 24V	27 30 40	2700K 3000K 4000K	BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass

5011-____

Example: 5011-30BBR

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

SPECIFICATIONS

Input:	24V DC			
Power:	1W to 18W / 2VA - 23VA			
Brightness:	50 lm to 1160 lm			
Beam Angle:	10° to 60°			
CRI:	85			
Rated Life:	70,000 hours			



ACCENT 24V 5011

WAC

LANDSCAPE LIGHTING

Accessories			
Accent Snoot	5010-SNOOT-BK 5010-SNOOT-BZ 5010-SNOOT-BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass	Shields lamp and reduces glare
6" Long Shroud	5010-LSHR-BK 5010-LSHR-BZ 5010-LSHR-BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass	Reduce glare. Ideal for downlighting application
Additional Stake	9000-ST9-BZ	Bronze	Durable PVC stake
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK	Bronze on Aluminum Bronze on Brass Black on Aluminum	Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ	Stainless Steel	Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Gutter Mount Bracket	5000-GM-BK	Stainless Steel	Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-ТСР-ВZ 5000-ТСР-ВК	Bronze on Aluminum Black on Aluminum	Bronze on Aluminum box with Stainless steel mounting screws. Two ½" NPT threaded holes
Optics	LENS-20-AMB Amber LENS-20-GRN Green LENS-20-RED Red	LENS-20-BLU Blue LENS-20-FR Frosted LENS-20-SPR Spread	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 4 in 5000-X04-BK 4 in 5000-X08-BK 8 in 5000-X08-BK 8 in 5000-X12-BZ 12 in 5000-X12-BK 12 in	5000-X18-BZ 18 in 5000-X18-BK 18 in 5000-X24-BZ 24 in 5000-X24-BK 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ	Bronze	

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 15 2021