TIKI LED AREA LIGHT

6041/6042



LANDSCAPE LIGHTING



Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION


Sturdy side mount design works well in applications where directional illumination is desired

FEATURES

- IP66 rated, Protected against powerful water jets
- Factory sealed water tight fixtures
- Solid diecast corrosion resistant aluminum alloy
- Recommended spacing for installation: Residential: 7 to 9ft; Commercial: 5 to 7ft
- Mounting stake, 6 foot lead wire, and direct burial gel filled wire nuts are included
- Maintains constant lumen output against voltage drop
- UL & cUL 1838 Listed

SPECIFICATIONS

Input: 24V DC 6.5W / 9.5VA Power: Brightness: 225 lm CRI: 90+ 60,000 hours Rated Life:




ORDERING NUMBER

	Color Temp		Finish	Finish	
6041 Tiki	27	2700K Warm White	BK	Black on Aluminum	
	30	3000K Pure White	BZ	Bronze on Aluminum	

6042-BK

Example: 6042-30BK



TIKI LED AREA LIGHT 6041/6042



Surface Mount Flange/Stake



Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box

Additional Mounting Stake



9000-ST9-BKDurable PVC stake





Guardian Mount

Heavy duty stainless steel spike to position fixture. Formed from a single piece of metal

9000-SP9-BZ Stainless Steel