

# TECHNICAL DATA SHEET

## 200CENT ROUND 1000LM ADJ TRIM IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable 0° - 25°

Ø43 mm - h = 100 mm

Material: Aluminium

### Ref N° 200 BL CR



Black Chrome - Nero Cromo  
Schwarz Chrom - Zwart Chrom  
Noir Chrome - Negro Cromo

Ask for a bespoke solution or your favorite RAL color

*Chiedete una soluzione personalizzata con il vostro colore RAL preferito*

*Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe*

*Vraag om een niet standaard afwerking of je favoriete RAL kleur*

Demandez une solution sur mesure ou votre couleur RAL préférée

*Solicite una solución a medida o su color favorito de la carta RAL*

### Ref N° 200 BL BL



Black Black - Nero Nero  
Schwarz Schwarz - Zwart Zwart  
Noir Noir - Negro Negro

### Ref N° 200 WH BL



White Black - Bianco Nero  
Weiß Schwarz - Wit Zwart  
Blanc Noir - Blanco Negro

### Ref N° 200 BL WH



Black White - Nero Bianco  
Schwarz Weiß - Zwart Wit  
Noir Blanc - Negro Blanco

### Ref N° 200 WH WH



White White - Bianco Bianco  
Weiß Weiß - Wit Wit  
Blanc Blanc - Blanco Blanco

### Ref N° 200 BL GO



Black Gold - Nero Oro  
Schwarz Gold - Zwart Goud  
Noir Or - Negro Oro

### Ref N° 200 WH GO



White Gold - Bianco Oro  
Weiß Gold - Wit Goud  
Blanc Or - Blanco Oro

### Ref N° 200 BL CO



Black Copper - Nero Rame  
Schwarz Kupfer - Zwart Koper  
Noir Cuivre - Negro Cobre

### Ref N° 200 WH CO



White Copper - Bianco Rame  
Weiß Kupfer - Wit Koper  
Blanc Cuivre - Blanco Cobre

### 200CENT ROUND ADJ IP20 TRIM 1000LM CRI 92

2700°K	3000°K
REF N° 533 26 930	REF N° 533 26 830

7,1 W - 1000LM - 2 step MacAdam - **A+**  
Serial wiring - - **CE** - -   
Requires remote LED driver - 600mA  
Perfect beam 28°

### INTEGRAL LED DRIVER

REF N° 697 66 015 15W DIM 1-10V Ø40 x 149mm

REF N° 697 36 015 15W DIM DALI Ø40 x 149mm

230V/50Hz - - - **CE** - IP20 - 600mA  
fits through the opening of Ø43mm

### REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

230V/50Hz - - current controlled  
 - **CE** - IP20 - 600mA - not dimmable

### REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W





1-10V DALI PUSH

REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH

REF N° 697 76 020 min 2W max 20W PHASE DIM

230V/50Hz - - current controlled  
 - **CE** - IP20 - 600mA - dimmable



### INSTALLATION KIT

REF N° 680 01 043 standard holesaw Ø 43 mm

### BEAM ANGLES

STANDARD (included) beam angle 28°