

# TECHNICAL DATA SHEET

## 200CENT ROUND 250LM FIX TRIMLESS IP20

INDOOR - INTERNO - INNERBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Fix (not adjustable) 0° - 0°

114x134 mm - h = 90 mm

Material: CALCYT® plaster



### Ref N° 200 BLACK

Black  
Nero  
Schwarz  
Zwart  
Noir  
Negro



### Ref N° 200 WHITE

White  
Bianco  
Weiß  
Wit  
Blanc  
Blanco



### Ref N° 200 CHROME

Chrome  
Cromo  
Chrom  
Chroom  
Chrome  
Cromo



### Ref N° 200 GOLD

Gold  
Oro  
Gold  
Goud  
Or  
Oro



### Ref N° 200 COPPER

Copper  
Rame  
Kupfer  
Koper  
Cuivre  
Cobre

### 200CENT ROUND FIX IP20 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 250 27 530	REF N° 250 27 930	REF N° 250 27 830	REF N° 250 27 730

3 W - 250LM - 2 step MacAdam - **A+**  
Serial wiring - - - -   
Requires remote LED driver - 1050mA  
Standard narrowbeam 12° - Optional 8° beam  
Ultra low glare (UGR < 13)

### REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 39W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled  
 - - IP20 - 1050mA - not dimmable




### REMOTE LED DRIVER DIM

REF N° 697 60 025 min.3W max. 60W

1-10V DALI PUSH

REF N° 697 70 050 min 2W max 45W PHASE DIM

230V/50Hz - - current controlled  
 - - IP20 - 1050mA - dimmable




### INSTALLATION KIT

**STANDARD** (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 200 99 025 installation system for gypsum ceiling 25 mm

REF N° 200 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box 200Cent - Galvanized steel



### BEAM ANGLES

**STANDARD** (included) beam angle 12°  
REF N° 203 20 008 (option) beam angle 8°

Ask for a bespoke solution or your favorite RAL color  
*Chiedere una soluzione personalizzata con il vostro colore RAL preferito*  
*Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe*  
*Vraag om een niet standaard afwerking of je favoriete RAL kleur*  
*Demandez une solution sur mesure ou votre couleur RAL préférée*  
*Solicite una solución a medida o su color favorito de la carta RAL*