

TECHNICAL DATA SHEET



200CENT ROUND 500LM FIX TRIM IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

Ø27 mm - h = 95 mm

Material: Aluminium



Ref N° 200 BLACK

Black
Nero
Schwarz
Zwart
Noir
Negro



Ref N° 200 WHITE

White
Bianco
Weiß
Wit
Blanc
Blanco



Ref N° 200 CHROME

Chrome
Cromo
Chrom
Chroom
Chrome
Cromo



Ref N° 200 GOLD

Gold
Oro
Gold
Goud
Or
Oro



Ref N° 200 COPPER

Copper
Rame
Kupfer
Koper
Cuivre
Cobre

200CENT ROUND FIX IP54 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 515 28 531	REF N° 515 28 931	REF N° 515 28 831	REF N° 515 28 731

5,9 W - 500LM - 2 step MacAdam - **A+**
Serial wiring - - **CE** - -
Requires remote LED driver - 700mA
Standard Perfectbeam 24°
Ultra low glare (UGR < 13)

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled
 - **CE** - IP20 - 700mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W

1-10V DALI PUSH

REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH

REF N° 697 77 010 min 2W max 10W PHASE DIM


REF N° 697 77 020 min 11W max 20W PHASE DIM

230V/50Hz - - current controlled
 - **CE** - IP20 - 700mA - dimmable

INSTALLATION KIT

REF N° 682 01 000 optimal leaf springs for concrete ceiling installation

REF N° 680 01 027 standard holesaw Ø 27 mm



BEAM ANGLES

STANDARD (included) beam angle 24°

Ask for a bespoke solution or your favorite RAL color
Chiedere una soluzione personalizzata con il vostro colore RAL preferito
Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe
Vraag om een niet standaard afwerking of je favoriete RAL kleur
Demandez une solution sur mesure ou votre couleur RAL préférée
Solicite una solución a medida o su color favorito de la carta RAL

WWW.BRICKINTHEWALL.EU

BRICK IN THE WALL®
invisible integration of light