

# TECHNICAL DATA SHEET




## 200CENT ROUND 750LM FIX TRIM IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

 Ø27 mm - h = 95 mm

Material: Aluminium



### Ref N° 200 BLACK

Black  
Nero  
Schwarz  
Zwart  
Noir  
Negro



### Ref N° 200 WHITE

White  
Bianco  
Weiß  
Wit  
Blanc  
Blanco



### Ref N° 200 CHROME

Chrome  
Cromo  
Chrom  
Chroom  
Chrome  
Cromo



### Ref N° 200 GOLD

Gold  
Oro  
Gold  
Goud  
Or  
Oro




### Ref N° 200 COPPER

Copper  
Rame  
Kupfer  
Koper  
Cuivre  
Cobre

### 200CENT ROUND FIX IP54 750LM CRI 92


2400°K	2700°K	3000°K	4000°K
REF N° 515 29 531	REF N° 515 29 931	REF N° 515 29 831	REF N° 515 29 731

6,2 W - 750LM - 2 step MacAdam - **A+**  
Serial wiring -  - **CE** -  -   
Requires remote LED driver - 250mA  
Standard beam angle 36°

### REMOTE LED DRIVER ON/OFF

REF N° 697 00 040 min.2W max. 30W

REF N° 697 00 080 min.27W max. 67W

230V/50Hz -  - current controlled  
 - **CE** - IP20 - 250mA - not dimmable

### REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 30W

1-10V DALI PUSH

REF N° 697 30 070 min 33W max 65W DALI

REF N° 697 60 080 min 27W max 67W 1-10V PUSH


REF N° 697 72 020 min 6W max 12,5W PHASE DIM

230V/50Hz -  - current controlled  
 - **CE** - IP20 - 250mA - dimmable

### INSTALLATION KIT

REF N° 682 01 000 optimal leaf springs for concrete ceiling installation

REF N° 680 01 027 standard holesaw Ø 27 mm



### BEAM ANGLES

STANDARD (included) beam angle 36°

Ask for a bespoke solution or your favorite RAL color  
*Chiedere una soluzione personalizzata con il vostro colore RAL preferito*  
Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe  
*Vraag om een niet standaard afwerking of je favoriete RAL kleur*  
Demandez une solution sur mesure ou votre couleur RAL préférée  
*Solicite una solución a medida o su color favorito de la carta RAL*

WWW.BRICKINTHEWALL.EU

**BRICK IN THE WALL®**  
invisible integration of light