

# TECHNICAL DATA SHEET




## 200CENT SQUARE 750LM FIX TRIMLESS IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Fix (not adjustable) 0° - 0°

 114x134 mm - h = 90 mm

Material : CALCYT® plaster



### REF N° 200 BLACK

Black  
Nero  
Schwarz  
Zwart  
Noir  
Negro








### REF N° 200 WHITE

White  
Bianco  
Weiß  
Wit  
Blanc  
Blanco

### 200CENT SQUARE IP20 750LM CRI 92




2400°K	2700°K	3000°K	4000°K
REF N° 520 29 530	REF N° 520 29 930	REF N° 520 29 830	REF N° 520 29 730

6,2 W - 750lm - 2 Step MacAdam -  **A+**  
Serial wiring -  -  -  -   
Requires remote LED driver - 250 mA  
Standard beam angle 36°

### REMOTE LED DRIVER ON/OFF

REF N° 697 00 040 min.1W max.30W

REF N° 697 00 080 min.27W max.67W




230V/50Hz -  - current controlled  
 -  - IP20 - 250mA - not dimmable

### REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max.30W  
1-10V DALI PUSH


REF N° 697 60 150 min.20W max.100W 1-10V

REF N° 697 30 150 min.20W max.100W DALI

230V/50Hz -  - current controlled  
 -  - IP20 - 250mA - dimmable

### INSTALLATION KIT

**STANDARD** (included) installation system for ceiling 9 - 12 - 15 mm  
**REF N° 200 99 025** installation system for gypsum ceiling 25 mm  
**REF N° 200 99 030** installation system for gypsum ceiling 30 mm  
**REF N° 827 00 000** Concrete box 200CENT - Galvanized steel



### BEAM ANGLES

**STANDARD** (included) beam angle 36°

