

# TECHNICAL DATA SHEET


## 200CENT SQUARE 250LM FIX TRIM IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

□ ∅32 mm - h = 95 mm

Material : Aluminium



### REF N° 200 BLACK

Black  
Nero  
Schwarz  
Zwart  
Noir  
Negro





### REF N° 200 WHITE

White  
Bianco  
Weiß  
Wit  
Blanc  
Blanco

### 200CENT SQUARE IP54 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 526 27 531	REF N° 526 27 931	REF N° 526 27 831	REF N° 526 27 731

3W - 250lm - 2 Step MacAdam -   
Serial wiring - - - -   
Requires remote LED driver - 1050mA   
Narrow beam 12° - Ultra low glare (UGR < 13)



### INSTALLATION KIT

REF N° 680 01 032 standard holesaw ∅32mm



### BEAM ANGLES

STANDARD (included) beam angle 12°

### REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 39W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled   
 - - IP20 - 1050mA - not dimmable

### REMOTE LED DRIVER DIM

REF N° 697 60 025 min. 2W max. 60W

1-10V DALI PUSH

230V/50Hz - - current controlled   
 - - IP20 - 1050mA - dimmable

