

TECHNICAL DATA SHEET


200CENT ROUND 750LM SWING 30 TRIMLESS IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Adjustable 0° - 27°

114x134 mm - h = 70 mm

Material: CALCYT® plaster



Black Black
Nero Nero
Schwarz Schwarz
Zwart Zwart
Noir Noir
Negro Negro

Ref N° 200 BL BL



White Black
Bianco Nero
Weiß Schwarz
Wit Zwart
Blanc Noir
Blanco Negro

Ref N° 200 WH BL



Black Chrome
Nero Cromo
Schwarz Chrom
Zwart Chrom
Noir Chrome
Negro Cromo

Ref N° 200 BL CR



White White
Bianco Bianco
Weiß Weiß
Wit Wit
Blanc Blanc
Blanco Blanco

Ref N° 200 WH WH



Black Gold
Nero Oro
Schwarz Gold
Zwart Goud
Noir Or
Negro Oro

Ref N° 200 BL GO



White Gold
Bianco Oro
Weiß Gold
Wit Goud
Blanc Or
Blanco Oro

Ref N° 200 WH GO



Black Copper
Nero Rame
Schwarz Kupfer
Zwart Koper
Noir Cuivre
Negro Cobre

Ref N° 200 BL CO



White Copper
Bianco Rame
Weiß Kupfer
Wit Koper
Blanc Cuivre
Blanco Cobre

Ref N° 200 WH CO



Bronze Bronze
Bronzo Bronzo
Bronze Bronze
Brons Brons
Bronze Bronze
Bronce Bronce

Ref N° 200 BR BR



Brass Brass
Ottone Ottone
Messing Messing
Messing Messing
Laiton Laiton
Latón Latón

Ref N° 200 ME ME



Gold Black
Oro Nero
Gold Schwarz
Goud Zwart
Or Noir
Oro Negro

Ref N° 200 GO BL



Gold Gold
Oro Oro
Gold Gold
Goud Goud
Or Or
Oro Oro

Ref N° 200 GO GO

200CENT ROUND SWING 30 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 551 29 530	REF N° 551 29 930	REF N° 551 29 830	REF N° 551 29 730

6,2 W - 750LM - 2 step MacAdam - **A+**
Serial wiring - - **CE** - -
Requires remote LED driver - 250mA
Standard beam angle 36°

REMOTE LED DRIVER ON/OFF

REF N° 697 00 040 min.2W max. 30W

REF N° 697 00 080 min.27W max. 67W

230V/50Hz - - current controlled
 - **CE** - IP20 - 250mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 30W



1-10V DALI PUSH

REF N° 697 30 070 min 33W max 65W DALI

REF N° 697 60 080 min 27W max 67W 1-10V PUSH

REF N° 697 72 020 min 6W max 12,5W PHASE DIM

230V/50Hz - - current controlled
 - **CE** - IP20 - 250mA - dimmable




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 200 99 025 installation system for gypsum ceiling 25 mm

REF N° 200 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box 200Cent - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°