

# TECHNICAL DATA SHEET



## 200CENT ROUND 1000LM SWING 30 TRIMLESS IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Adjustable 0° - 27°

114x134 mm - h = 70 mm

Material: CALCYT® plaster



### 200CENT ROUND SWING 30 1000LM CRI 92

2700°K	3000°K
REF N° 551 26 930	REF N° 551 26 830

7,1 W - 1000LM - 2 step MacAdam - **A+**  
Serial wiring - - **CE** - -   
Requires remote LED driver - 600mA  
Perfect beam 28°

### REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

230V/50Hz - - current controlled  
 - **CE** - IP20 - 600mA - not dimmable

### REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W



1-10V DALI PUSH

REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH

REF N° 697 76 020 min 2W max 20W PHASE DIM

230V/50Hz - - current controlled  
 - **CE** - IP20 - 600mA - dimmable




### INSTALLATION KIT

**STANDARD** (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 200 99 025 installation system for gypsum ceiling 25 mm

REF N° 200 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box 200Cent - Galvanized steel



### BEAM ANGLES

**STANDARD** (included) beam angle 28°