

TECHNICAL DATA SHEET



200CENT ROUND 250LM SWING 90 TRIM IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Adjustable 0° - 90°

Ø27 mm - h = 70 mm

Material: Aluminium



200CENT ROUND SWING 90 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 553 27 530	REF N° 553 27 930	REF N° 553 27 830	REF N° 553 27 730

3 W - 250LM - 2 step MacAdam - **A+**
Serial wiring - - - -
Requires remote LED driver - 1050mA
Standard narrowbeam 12° - Optional 8° beam
Ultra low glare (UGR < 13)

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 39W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled
 - - IP20 - 1050mA - not dimmable



REMOTE LED DRIVER DIM

REF N° 697 60 025 min.3W max. 60W

1-10V DALI PUSH


REF N° 697 70 050 min 2W max 45W PHASE DIM

230V/50Hz - - current controlled
 - - IP20 - 1050mA - dimmable



INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø 27 mm



BEAM ANGLES

STANDARD (included) beam angle 12°
REF N° 203 20 008 (option) beam angle 8°