

## Simply pillar medium up/down

### General

Location:	Exterior
Class:	CE (Class III)
IP-rating:	IP67
Driver included:	Yes
Installation orientation:	Wall
Main material:	Weathered brass

Dimensions (mm): H: 250mm W: 120mm D: 50mm

Lamp included:	Yes (Integral)
Dimmable:	No (Dimmable on request)

### Models



**CODE** NNA-021-T25 LED

Simply pillar up/down 25cm weathered brass

120° - 2700K - CRI>90  
2xLED 6W - 400lm - 350mA

### General

Location:	Exterior
Class:	CE (Class III)
IP-rating:	IP67
Driver included:	Yes
Installation orientation:	Wall
Main material:	Stainless steel 304 powder coated

Dimensions (mm): H: 250mm W: 120mm D: 50mm

Lamp included:	Yes (Integral)
Dimmable:	No (Dimmable on request)

### Models



**CODE NNA-021-T25 INOXLED**

Simply pillar up/down 25cm brushed inox

120° - 2700K - CRI>90  
2xLED 6W - 400lm - 350mA



**CODE NNA-023-T25 ALULED**

Simply pillar up/down 25cm chrome

120° - 2700K - CRI>90  
2xLED 6W - 400lm - 350mA



**CODE NNA-021-T25 ALULED**

Simply pillar up/down 25cm black

120° - 2700K - CRI>90  
2xLED 6W - 400lm - 350mA



**CODE NNA-022-T25 ALULED**

Simply pillar up/down 25cm white

120° - 2700K - CRI>90  
2xLED 6W - 400lm - 350mA



— **CODE** NNA-028-T25 ALULED

Simply pillar up/down 25cm braungrau

120° - 2700K - CRI>90  
2xLED 6W - 400lm - 350mA



— **CODE** NNA-021-T25 DBLED

Simply pillar up/down 25cm dark bronze

120° - 2700K - CRI>90  
2xLED 6W - 400lm - 350mA

## Simply colors

