

General

Location:	Exterior
Class:	CE (Class III)
IP-rating:	IP67
Driver included:	Yes
Installation orientation:	Wall
Main material:	Weathered brass

Dimensions (mm): H: 250mm W: 120mm D: 50mm

Lamp included: Yes (Integral)
Dimmable: No (Dimmable on request)

Models



CODE NNA-024-T25 LED

Simply pillar down 25cm weathered brass

120° - 2700K - CRI>90
1xLED 6W - 400lm - 350mA

Simply pillar medium down

General

Location:	Exterior
Class:	CE (Class III)
IP-rating:	IP67
Driver included:	Yes
Installation orientation:	Wall
Main material:	Stainless steel 304 powder coated

Dimensions (mm): H: 250mm W: 120mm D: 50mm

Lamp included: Yes (Integral)
Dimmable: No (Dimmable on request)

Models



CODE NNA-024-T25 INOXLED

Simply pillar down 25cm brushed inox

120° - 2700K - CRI>90
1xLED 6W - 400lm - 350mA



CODE NNA-027-T25 ALULED

Simply pillar down 25cm chrome

120° - 2700K - CRI>90
1xLED 6W - 400lm - 350mA



CODE NNA-025-T25 ALULED

Simply pillar down 25cm black

120° - 2700K - CRI>90
1xLED 6W - 400lm - 350mA



CODE NNA-026-T25 ALULED

Simply pillar down 25cm white

120° - 2700K - CRI>90
1xLED 6W - 400lm - 350mA



— **CODE** NNA-029-T25 ALULED

Simply pillar down 25cm braungrau

120° - 2700K - CRI>90
1xLED 6W - 400lm - 350mA



— **CODE** NNA-024-T25 DBLED

Simply pillar down 25cm dark bronze

120° - 2700K - CRI>90
1xLED 6W - 400lm - 350mA

Simply colors

