

General

Location:	Exterior
Class:	CE (Class III)
IP-rating:	IP67
Driver included:	Yes
Installation orientation:	Ground
Main material:	Weathered brass

Dimensions (mm): H: 700mm W: 100mm D: 100mm

Lamp included:	Yes (Integral)
Dimmable:	No (Dimmable on request)

Models



CODE NNA-012-T35 LED (*)

Simply bollard 90° 35cm weathered brass

120° - 2700K - CRI>90
1xLED 6W - 400lm - 350mA



CODE NNA-012-T70 LED (*)

Simply bollard 90° 70cm weathered brass

120° - 2700K - CRI>90
1xLED 6W - 400lm - 350mA

Required options (*)

NNA-011-TBASE

or

NNA-011-TPIC

U-base for installation on paved surfaces

Ground spike for installation in loose ground

General

Location: Exterior
 Class: CE (Class III)
 IP-rating: IP67
 Driver included: Yes
 Installation orientation: Ground
 Main material: Stainless steel 304 powder coated

Dimensions (mm): H: 700mm W: 100mm D: 100mm

Lamp included: Yes (Integral)
 Dimmable: No (Dimmable on request)

Models



CODE NNA-012-T70 INOXLED (*)

Simply bollard 90° 70cm brushed inox

120° - 2700K - CRI>90
 1xLED 6W - 400lm - 350mA



CODE NNA-012-T70 ALULED (*)

Simply bollard 90° 70cm braungrau

120° - 2700K - CRI>90
 1xLED 6W - 400lm - 350mA



CODE NNA-015-T70 ALULED (*)

Simply bollard 90° 70cm black

120° - 2700K - CRI>90
 1xLED 6W - 400lm - 350mA



CODE NNA-015-T70 DBLED (*)

Simply bollard 90° 70cm dark bronze

120° - 2700K - CRI>90
 1xLED 6W - 400lm - 350mA

Required options (*)

NNA-011-TBASE
 or
 NNA-011-TPIC

U-base for installation on paved surfaces

Ground spike for installation in loose ground