

## General

Location:	Exterior
Class:	CE (Class III)
IP-rating:	IP67
Driver included:	Yes
Installation orientation:	Wall
Main material:	Weathered brass
Dimensions (mm):	H: 700mm W: 100mm D: 100mm
Lamp included:	Yes (Integral)
Dimmable:	No (Dimmable on request)

## Models



### CODE NNA-011-T35 LED (\*)

Simply bollard 35cm weathered brass

120° - 2700K - CRI>90  
1xLED 6W - 400lm - 350mA



### CODE NNA-011-T70 LED (\*)

Simply bollard 70cm weathered brass

120° - 2700K - CRI>90  
1xLED 6W - 400lm - 350mA

## Required options (\*)

NNA-011-TBASE

or

NNA-011-TPIC

U-base for installation on paved surfaces

Ground spike for installation in loose ground

## General

Location:	Exterior
Class:	CE (Class III)
IP-rating:	IP67
Driver included:	Yes
Installation orientation:	Wall
Main material:	Stainless steel 304 powder coated

Dimensions (mm): H: 700mm W: 100mm D: 100mm

Lamp included:	Yes (Integral)
Dimmable:	No (Dimmable on request)

## Models



**CODE NNA-013-T70 ALULED (\*)**

Simply bollard 70cm braungrau

120° - 2700K - CRI>90  
1xLED 6W - 400lm - 350mA



**CODE NNA-014-T70 ALULED (\*)**

Simply bollard 70cm black

120° - 2700K - CRI>90  
1xLED 6W - 400lm - 350mA



**CODE NNA-014-T70 DBLED (\*)**

Simply bollard 70cm dark bronze

120° - 2700K - CRI>90  
1xLED 6W - 400lm - 350mA

## Required options (\*)

**NNA-011-TBASE**

or

**NNA-011-TPIC**

U-base for installation on paved surfaces

Ground spike for installation in loose ground

General dimensions

