Mired

WK-EOS CONTROL MODULE FOR RAKO WIRED SYSTEMS

WHAT IS IT ?

data sheet

A hard wired 6 button push button control module.

Customisable and programmable using Rasoft Pro Software.

Rako EOS screwless plate kits are available in the following selection of finishes:

Matt White (WH)

Matt Black (MB)

Satin Chrome (SC)

Polished Chrome (PC)

Matt Bronze (BM)

Antique Brass (AB)

Polished Brass (PB)

Electronics and coverplate supplied separately.

EOS coverplate kits use the code: WP-EOS-XX-XX

Shown opposite:

WK-EOS-6 module complete with WP-EOS-60-BM cover plate kit fitted. WK-EOS wired push button wall plate controller. Customisable and programmable via RASOFT Pro.



The WK-EOS push button wired control module is programmable via Rako's Rasoft Pro software. Each input is fully customisable and can be addressed to separate Rako Rooms or Channels and activate on press or release, giving a 'Press and Hold' function. Each button is complete with a blue LED indicator, additionally, each input can trigger an internal macro function.

Easy connection to the Rakom wired CAT5 network is by a removable 8 way Krone punch down module that can be installed at first fix stage prior to the push button front control module. This protects the control module from being damaged while building works are being finished.

WK-EOS control modules are designed to be flush mounted to a UK back-boxes






data sheet WK-EOS ONTROL MODULE FOR RAKO WIRED SYSTEMS

technical data


dimensions	PCB: 50x50x35mm - flush mount only Cover Plate: 88x88x3mm
input supply	12-18vdc supply from Rakom CAT5 wired network.
fixing	Flush mounting into standard UK single gang back box, minimum 35mm deep.
weight	Electronics 37g Plate & Grid 141g
climate range	Temperature +2C to +40C Humidity +5% to 95% non condensing.
cable type	UTP CAT5e or CAT6
terminal type	8 way Krone punch down (screw terminal option available)
standards	Emissions - EN61000-6-3 : 2007 Immunity - EN61000-6-1 : 2007
communication	Rakom wired network
memory	Flash memory (non volatile) Firmware upgrades via RASOFT programming software

mechanical data





35mm




Standard button configurations & part numbers

•	۸٥
0••	۷ ۰
0	00

WP-EOS-60-XX

Λ.
0
V





WP-EOS-31-XX

telephone +44 (0) 1634 226666 www.rakocontrols.com

WP-EOS-61-XX

WE RESERVE THE RIGHT TO CHANGE THE SPECIFICATION AND DATA HEREWITH WITHOUT NOTICE © 2022 RAKO CONTROLS LIMITED