

Wireless

data sheet

RK-MOD

CONTROL MODULE FOR RAKO WIRELESS SYSTEMS



WHAT IS IT ?

A wireless push button module that can accommodate up to 12 push buttons configurable via NFC. Standard button configurations are shown overleaf, along with their corresponding part numbers.

Hand finished metal surrounds are available in a number of finishes and should be ordered separately;

Satin Chrome: HS-MOD-SC

Polished Chrome: HS-MOD-PC

Antique Brass: HS-MOD-AB

Polished Brass: HS-MOD-PB

Matt Bronze: HS-MOD-BM

Matt White: HS-MOD-WH

Matt Black: HS-MOD-MB

Powered by lithium battery allows the RK-MOD-xxx-x to be mounted anywhere without the need to run cables.

The keypad opposite shows:

RK-MOD-110-B with HS-MOD-SC surround.

Product code Key:

RK-MOD	XXX	X
Product	Button	Button
prefix code	Layout	colour
RK-MOD	070	B (Black)
	110	
	020 etc. see	
	overleaf for	
	full range	

Wireless push button wall plate with up to 12 push buttons. Customisable and programmable via NFC communication



SIMPLE, FLEXIBLE CONTROL

The RK-MOD-xxx-x uses three different button sizes across a range of keypad layouts. This offers a truly flexible range of designs to suit all your lighting control requirements including: Curtain, Blind, Audio, Multi and Single Room layouts.

A RAMPI or RK-HUB and Rasoft Pro programming software is required for setup and configuration of the RK-MOD-xxx-x. Once addressed it is possible to control any Room/Channel in the system, sending commands to each including:

- Scene selection
- Scene toggle
- Level toggle
- Room/Channel raise & lower
- Macro start/stop/control
- House Master controls

Rako's coded radio transmission eliminates the need for any data cables ensuring the system can be installed with minimum fuss or disruption.



Wireless

data sheet

RK-MOD

CONTROL MODULE FOR RAKO WIRELESS SYSTEMS




technical data Control Panel: 86x86x25mm Surround: 88x88x6mm Flush mounting into standard UK single gang back box, minimum depth: 25mm 6V DC - 2x 3V Lithium coin cell CR2016 (remote power supply version available) 95g weight Greater than 3 years climate range

86mm 25mm 86mm

mechanical data

Temperature +2C to +40CHumidity +5% to 95% non condensing 433.9MHz coded FM radio Programming via NFC



Standard button configurations & part numbers

Flash memory (non volatile)

Firmware upgrade via Rasoft Pro

Emissions - EN61000-6-3: 2007 Immunity - EN61000-6-1: 2007

Scene 1	Scene 3
Scene i	Scene 3
Scene 2	Scene 4
Off	۸
	v
RK-MOD-	070

memory

Scene 1	Scene 3
Scene 2	Scene 4
Off	On
	Off

Scene 5
Scene 6
Scene 7
Scene 8
۸
٧


RK-MOD-110

Scene 1	Scene 1
Scene 2	Scene 2
Scene 3	Scene 3
Scene 4	Scene 4
Off	Off

RK-MOD-103

Scene 1	Open
Scene 2	•
Scene 3	Close
Scene 4	
Off	۸
	v

RK-MOD-101



RK-MOD-111

RK-MOD-072

On	۸		On	On
Off	v		Off	Off
RK-MOD-	040	-	RK-MOD	-041

On	
Off	
RK-MOD-	-020

Open	Open
_	
•	•
Close	Close
RK-MOD-	-060
RK-MOD	-060

•		
Close		