

OPIS CEILING

IP40 IK07    

TIPOLOGIA / TYPOLOGY


Plafone | Ceiling mounted

POSIZIONE INSTALLATIVA | INSTALLATION POSITION

A soffitto | On ceiling


AMBIENTE INSTALLATIVO | INSTALLATION LOCATION

Interno | Indoor



OPIS CEILING - S

3,5W




OPIS CEILING - M

10W



kg 0,99



OPIS CEILING - L

20W



kg 1,32

OPIS CEILING

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	S version: 3,5W - M Version: 10W - L version: 20W
ALIMENTAZIONE POWER SUPPLY	230Vac
FREQUENZA FREQUENCY	50/60 Hz
ALIMENTATORE POWER SUPPLY UNIT	Integrato Integrated
COLLEGAMENTO CONNECTION	Tensione di rete Mains voltage

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	S version: 2200K, 2700K, 3000K, 4000K, red, green, blue M and L version: 2700K, 3000K, 4000K
INDICE RESA CROMATICA CRI CRI	S, M and L version: >90 (2700K, 3000K, 4000K)
INDICE RESA CROMATICA CRI CRI	S version: >80 (2200K)
BINNING	3 step MacAdam 3 MacAdam steps
OTTICHE OPTICS	S version: 30° M version: 30°, 60° L version: 18°, 30°, 55°
UGR	<19
FLUSSO REALE EMESSE - 3000K REAL OUTPUT FLUX	S: 3,5W 174lm 30° M: 10W 702lm 30° L: 20W 1792lm 30°
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES

PESO WEIGHT	S version: kg 0,49 - M Version: kg 0,98 - L version: kg 1,32
FINITURE FINISHES	Bianco txt, Grigio txt, Nero txt, Corten, Sand <i>Txt White, txt Grey, txt Black, Corten, Sand</i>
INSTALLAZIONE INSTALLATION	A plafone tramite staffa (inclusa) e viti di fissaggio (non incluse) <i>Ceiling mounted with bracket (included) and fixing screws (not included)</i>
MATERIALE MATERIAL	Corpo in alluminio, schermo in metacrilato opalino <i>Aluminium body, opal methacrylate shield</i>

CARATTERISTICHE GENERALI | GENERAL FEATURES

TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP40
GRADO DI RESISTENZA IMPACT RESISTANCE	IK07
GLOW WIRE TEST GLOW WIRE TEST	960°C
TEMPERATURA SCHERMO SCREEN TEMPERATURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	I
CALPESTABILE WALKOVER	No
CARRABILE DRIVE OVER	No
SICUREZZA STANDARD STANDARD SAFETY	/
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1