




ARKE SQUARE - S 24Vdc

IP67 IK08 CE III WP | A > A+ > A++

TIPOLOGIA / *TYPOLGY*Incasso | *Recessed*POSIZIONE INSTALLATIVA | *INSTALLATION POSITION*A terra o a parete | *Floor or wall mounting*AMBIENTE INSTALLATIVO | *INSTALLATION LOCATION*Esterno | *Outdoor*

ARKE SQUARE - S

2,2W

Kg 0,14



CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	2,2W
ALIMENTAZIONE POWER SUPPLY	24Vdc
ALIMENTATORE POWER SUPPLY UNIT	2,2W - 24Vdc Non incluso Not included
COLLEGAMENTO CONNECTION	Parallelo Parallel

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	2200K, 2700K, 3000K, 4000K, Red, Green, Blue
INDICE RESA CROMATICA CRI CRI	>80 (2200K, 2700K, 3000K, 4000K)
BINNING	3 step MacAdam 3 MacAdam steps
OTTICHE OPTICS	10°, 36°, 60°, 10°x 55°
FLUSSO REALE EMESSO - 3000K REAL OUTPUT FLUX	2,2W 127lm 36°
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES

PESO WEIGHT	Kg 0,14
FINITURE FINISHES	Vetro - Grigio opaco, Vetro - Nero opaco Glass - Matt Grey, Glass - Matt Black
INSTALLAZIONE INSTALLATION	A incasso a terra con cassaforma (non inclusa), a incasso su muratura con cassaforma (non inclusa) Recessed on ground with housing box (not included), recessed on brickwork with housing box (not included)
MATERIALE MATERIAL	Corpo in alluminio anticorodal, vetro temperato serigrafato Anticorodal aluminium body, silk-screen printed tempered glass

CARATTERISTICHE GENERALI | GENERAL FEATURES


TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP67
GRADO DI RESISTENZA IMPACT RESISTANCE	IK08
GLOW WIRE TEST GLOW WIRE TEST	960°C
TEMPERATURA MASSIMA APPARECCHIO MAX. TEMPERATURE OF FIXTURE	45° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	III
CALPESTABILE WALKOVER	Sì / Yes
CARRABILE DRIVE OVER	2000 Kg
SICUREZZA STANDARD STANDARD SAFETY	WP System
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1



ARKE SQUARE - S 24Vdc

ACCESSORI | ACCESSORIES

CODICE CODE	CIQ32		
TIPOLOGIA TYPOLOGY	Cassaforma Housing box		kg 0,06
MATERIALE MATERIAL	PVC, PLA jig PVC, Dima in PLA		



FILTRI | FILTER

CODICE / CODE	HC
TIPOLOGIA / TYPOLOGY	Filtro Honeycomb Honeycomb filter

