

MINIJOS S2

Surface projectors

design Roberto Mantovani



A projector for wall or ceiling installation, it is characterised by a minimal design and high optical performance. It lends itself to applications ranging from accent lighting to general illumination.

Proiettore per installazione a parete o a soffitto connotato da un design minimale ed elevate prestazioni ottiche. Si presta ad applicazioni che vanno dalla luce d'accento all'illuminazione generale.

Projecteur pour installation murale ou sur plafond, caractérisé par un design minimaliste et de hautes performances optiques. Il est indiqué pour les applications allant de l'éclairage d'accentuation à l'éclairage général.

Projektor für Wand- oder Deckenmontage, der sich durch ein minimalistisches Design und eine hohe optische Leistung auszeichnet. Eignet sich für Anwendungen, die von der Akzentbeleuchtung bis zur Allgemeinbeleuchtung reichen.

IP20 made in Italy

Supply current
24VDC


Power
2W

Parallel wiring


CRI
85

2-Step MacAdam

Dimensions



Photometric diagrams




CCT/CRI/Flux

2700K	128 lm
3000K	133 lm
4200K	154 lm

Code construction

Note: Versions with extended arm length are available upon request.

MJSS2 X X X



Drivers 24VDC

on/off

AL2124 (1..5) IP20 28 mm

AL2012 (1..12) IP20 60 mm

AL2031 (1..35) IP20 70 mm

dimmable

AL5012 (1..12) IP20 DALI 2 PUSH 0/1..10V 45 mm

dimming module

AL7035 IP20 DALI 2 PUSH 0/1..10V 44 mm

Note: Dimming module AL7035 to be used in combination with a 24VDC power supply.