NEBO LED 1-R PLASTER IN ADJUSTABLE DOWNLIGHT

TRUE COLOUR CRI 98 | IP65

DLD/NEBO-A

DETAILS

Type	Adjustable 25°
IP Rating	IP65
IP Zone	Zone 1
Class	I
Standards	CE
Fire Rated	With accessory
Material	Aluminium
Cable	2 Core 0.5mm2
Cable Length	400mm
Warranty	5 Years

KEY POINTS

- True Colour CRI 98, amazingly high level of colour rendering
- R9 95, reds are redder than ever
- Simple access to the light engine for easy maintenance
- Dim to dark with our range of fully tested drivers

DIMENSIONS

Fitted Dims:	Ø60mm
Light Engine:	Ø59.4mm, H.94mm
Plaster Kit:	102 x 103mm H.30mm
Cutout:	Ø65mm
Fire Ring Cutout:	Ø71mm

NEBO LED 1-R PLASTER IN ADJUSTABLE DOWNLIGHT

TRUE COLOUR CRI 98 | IP65

DLD/NEBO-A

DLD ARCHITECTURAL

PRODUCT CODE CONSTRUCTION

MODEL		VERSION		FINISH		BAFFLE		BEAM ANGLE		LIGHT TEMP. CCT		DRIVER
DLD/NEBO	-	A	-	W	-	B	-	36D	-	27K	-	MD
		A Adjustable Plaster-In		W White B Black		W White B Black		36D 36°		27K 2700K 30K 3000K 4000K on request		MD No driver 010 TRIAC dim. 0-10V dim. D DALI dim.

SPECIFICATION

BEAM ANGLE	**36°**	
Delivered lumens* *(Tc 85°C, +/-7%)	700 lm	
Efficacy Lm/W	55 lm/W	
CCT	**2700K**	**3000K**
Binning SDCM (Hot)	2	
CRI	98	
R9	95	
TM30 Rf Rg	Rf 95 Rg 95	
LED Type	Luminus Gen. 6 CXM-6 COB LED	
LED Lifetime (Ave.)	50,000 hrs	
POWER		
Wattage	13W	
Voltage	220-240 V	
Voltage Output	43.33V	
Current	300mA	
DRIVER		
Supported Protocols	Mains Dim / TRIAC / 0-10V / DALI / Bluetooth	
Dim to Dark	0.1% Lux	
Distance from Luminaire	20m maximum	
Wiring	Series	
Emergency	Emergency packs available	

01189 889414

sales@darklightdesign.com

darklightdesign.com

Darklight Design
Unit 10 Brookside Business Centre
Church Road
Swallowfield
Reading
Berkshire
RG7 1TH