

Audy-In



Choose beam:
M=medium 23° or
W=wide 40°

350mA - **required driver see below**

1 x LED array 6,25W (LED incl.) - 350mA - 2700K (633lm) or 3000K (673lm) - CRI >95

*FALSE ceiling= aperture: Ø47 - depth: min. 70mm (driver in ceiling) / depth: min. 40mm (driver remote)

*CONCRETE ceiling= aperture: Ø47 - depth: min. 90mm (driver remote)

materials: brass, aluminium

*Required free air area, see www.trizo21.com/requiredarea - CEILING - IP50

FALSE & CONCRETE ceiling



		FRAME brass	FRAME black	FRAME white	FRAME gunmetal	FRAME bronze	FRAME nickel
2700K	AUDY 1273	AUDY 1272	AUDY 1271		AUDY 1274	AUDY 1277	AUDY 1279
2700K							
3000K	AUDY 1303	AUDY 1302	AUDY 1301		AUDY 1304	AUDY 1307	AUDY 1309
3000K							
+ honeycomb	2700K	AUDY 1273H	AUDY 1272H	AUDY 1271H			
+ honeycomb	2700K				AUDY 1274H	AUDY 1277H	AUDY 1279H
+ honeycomb	3000K	AUDY 1303H	AUDY 1302H	AUDY 1301H			
+ honeycomb	3000K				AUDY 1304H	AUDY 1307H	AUDY 1309H

REQUIRED DRIVER

DEVICE	DIM.	DRIVER	VOLT
1 x	LC (TRIAC/IGBT)	D 6WT	230V
2 x	LC (TRIAC/IGBT)	D 18WT	230V
1-2 x	PU (PUSH-DIM) + 1-10 (1-10V)	D 15WP	110V-230V
1-2 x	PU (PUSH-DIM) + DA (DALI)	D 15WDA EU	230V
1-2 x	DA (DALI)	D 15WDA EU-US	110V-230V
2-6 x	PU (PUSH-DIM) + DA (DALI) + 1-10 (1-10V)	D 40WDP	110V-230V

driver remote: does not fit through cutout hole of fixture

For warranty use only Trizo21® supplied LED drivers as mentioned. For all specs and techs about drivers, see www.trizo21.com/drivers