



◆ Choose beam:
 M=medium 23° or
 W=wide 40°

Audy-In BATHROOM

350mA - **required driver see below**

1 x LED array 6,25W (incl.) - 350mA - 2700K (633lm) or 3000K (673lm) - CRI >95

***FALSE ceiling**= aperture: Ø47 - depth: min. 70mm (driver in ceiling) / depth: min. 40mm (driver remote)

***CONCRETE ceiling**= aperture: Ø47 - depth: min. 90mm (driver remote)

materials: brass, aluminium

*Required free air area, see www.trizo21.com/requiredarea - **CEILING - IP55** ◆◆◆

FALSE & CONCRETE ceiling



	FRAME brass	FRAME black	FRAME white	FRAME gunmetal	FRAME bronze	FRAME nickel
2700K	AUDEX 1273 ◆	AUDEX 1272 ◆	AUDEX 1271 ◆	AUDEX 1274 ◆	AUDEX 1277 ◆	AUDEX 1279 ◆
2700K						
3000K	AUDEX 1303 ◆	AUDEX 1302 ◆	AUDEX 1301 ◆	AUDEX 1304 ◆	AUDEX 1307 ◆	AUDEX 1309 ◆
3000K						

REQUIRED DRIVER

DEVICE	DIM.	DRIVER	VOLT
1 x	LC (TRIAC/IGBT)	D 6WT*	230V
2 x	LC (TRIAC/IGBT)	D 18WT	230V
1-2 x	PU (PUSH-DIM) + 1-10 (1-10V)	D 15WP	110V-230V
1-2 x	PU (PUSH-DIM) + DA (DALI)	D 15WDA EU	230V
1-2 x	DA (DALI)	D 15WDA EU-US	110V-230V
2-6 x	PU (PUSH-DIM) + DA (DALI) + 1-10 (1-10V)	D 40WDP	110V-230V

driver remote: does not fit through cutout hole of fixture

*IP 44

For warranty use only Trizo21® supplied LED drivers as mentioned. For all specs and techs about drivers, see www.trizo21.com/drivers