



Choose beam:  
M=medium 23° or  
W=wide 40°

! driver remote mounting excl.

# Audy-Wall 1S

500mA - **required remote mounted driver see below**

1 x LED array 4,32W (LED incl.) - 500mA - 2700K (487lm) or 3000K (517lm) - CRI >95

materials: brass, aluminium

WALL - IP50



FRAME brass  
RING brass

FRAME black  
RING black

FRAME white  
RING white

FRAME gunmetal  
RING gunmetal

FRAME bronze  
RING bronze

FRAME nickel  
RING nickel

2700K

2700K

3000K

3000K

ATWS 1273

ATWS 1272

ATWS 1271

ATWS 1274

ATWS 1277

ATWS 1279

ATWS 1303

ATWS 1302

ATWS 1301

ATWS 1304

ATWS 1307

ATWS 1309

## REQUIRED REMOTE MOUNTED DRIVER

DEVICE	DIM.	DRIVER	VOLT
1 x	(TRIAC/IGBT)		230V
2 x	(TRIAC/IGBT)		230V
1-4 x	(PUSH-DIM) +  (1-10V)		110V-230V
1-4 x	(DALI)		110V-230V
1-12 x	(PUSH-DIM) +  (DALI) +  (1-10V)		110V-230V

driver remote: does not fit through cutout hole of fixture

For warranty use only Trizo21® supplied LED drivers as mentioned. For all specs and techs about drivers, see [www.trizo21.com/drivers](http://www.trizo21.com/drivers)