

▲ Choose beam upper lightsource:

M=medium 23° or W=wide 40°

▼ Choose beam lower lightsource:

M=medium 23° or W=wide 40°

! driver remote mounting excl.


Audy-Wall 2S

500mA - **required remote mounted driver see below**

2 x LED array 4,32W (LED incl.) - 500mA - 2700K (2 x 487lm) or 3000K (2 x 517lm) - CRI >95

materials: brass, aluminium

WALL - IP50



FRAME brass
RING brass



FRAME black
RING black



FRAME white
RING white



FRAME gunmetal
RING gunmetal



FRAME bronze
RING bronze



FRAME nickel
RING nickel



2700K

ATWD 2273 ▲▼

ATWD 2272 ▲▼

ATWD 2271 ▲▼

ATWD 2274 ▲▼

ATWD 2277 ▲▼

ATWD 2279 ▲▼

2700K

3000K

ATWD 2303 ▲▼

ATWD 2302 ▲▼

ATWD 2301 ▲▼

ATWD 2304 ▲▼

ATWD 2307 ▲▼

ATWD 2309 ▲▼

3000K

REQUIRED REMOTE MOUNTED DRIVER

DEVICE	DIM.	DRIVER	VOLT
1 x	LC (TRIAC/IGBT)	D 10WT500	230V
1-2 x	PU (PUSH-DIM) + 1-10 (1-10V)	D 15WP	110V-230V
1-2 x	DA (DALI)	D 15WDA EU-US	110V-230V
1-4 x	PU (PUSH-DIM) + DA (DALI) + 1-10 (1-10V)	D 40WDP	110V-230V

driver remote: does not fit through cutout hole of fixture

For warranty use only Trizo21® supplied LED drivers as mentioned. For all specs and techs about drivers, see www.trizo21.com/drivers