


Audy-Solitaire RL



RL= long vertical rod 750mm + powercord - Longer lengths available **on demand**
 350mA - **required driver see below**

1 x LED array 6,25W (**LED incl.**) - 350mA - 2700K (633lm) or 3000K (673lm) - CRI >95

FALSE ceiling= aperture: Ø45 - depth: min. 70mm (driver in ceiling) / depth: min. 50mm (driver remote)




CONCRETE ceiling= aperture: Ø45 - depth: min. 40mm (driver remote)

material: brass

SUSPENSION - IP40

Choose beam:
 M=medium 23° or
 W=wide 40°

POWERCORD LENGTH




FALSE ceiling



L 1000	2700K	AUCA 1232						
L 1000	2700K		AUCA 1222	AUCA 1211				
L 1000	2700K				AUCA 1242	AUCA 1272	AUCA 1292	
L 1000	3000K	AUCA 1332						
L 1000	3000K		AUCA 1322	AUCA 1311				
L 1000	3000K				AUCA 1342	AUCA 1372	AUCA 1392	

+ honeycomb	L 1000	2700K	AUCA 1232H					
+ honeycomb	L 1000	2700K		AUCA 1222H	AUCA 1211H			
+ honeycomb	L 1000	2700K				AUCA 1242H	AUCA 1272H	AUCA 1292H
+ honeycomb	L 1000	3000K	AUCA 1332H					
+ honeycomb	L 1000	3000K		AUCA 1322H	AUCA 1311H			
+ honeycomb	L 1000	3000K				AUCA 1342H	AUCA 1372H	AUCA 1392H

CONCRETE ceiling



L 1000	2700K	AUCC 1232						
L 1000	2700K		AUCC 1222	AUCC 1211				
L 1000	2700K				AUCC 1242	AUCC 1272	AUCC 1292	
L 1000	3000K	AUCC 1332						
L 1000	3000K		AUCC 1322	AUCC 1311				
L 1000	3000K				AUCC 1342	AUCC 1372	AUCC 1392	

+ honeycomb	L 1000	2700K	AUCC 1232H					
+ honeycomb	L 1000	2700K		AUCC 1222H	AUCC 1211H			
+ honeycomb	L 1000	2700K				AUCC 1242H	AUCC 1272H	AUCC 1292H
+ honeycomb	L 1000	3000K	AUCC 1332H					
+ honeycomb	L 1000	3000K		AUCC 1322H	AUCC 1311H			
+ honeycomb	L 1000	3000K				AUCC 1342H	AUCC 1372H	AUCC 1392H

REQUIRED DRIVER

DEVICE	DIM.	DRIVER	VOLT
1 x	LC (TRIAC/IGBT)	D 6WT	230V
2 x	LC (TRIAC/IGBT)	D 18WT	230V
1-2 x	PU (PUSH-DIM) + 1-10 (1-10V)	D 15WP	110V-230V
1-2 x	PU (PUSH-DIM) + DA (DALI)	D 15WDA EU	230V
1-2 x	DA (DALI)	D 15WDA EU-US	110V-230V
2-6 x	PU (PUSH-DIM) + DA (DALI) + 1-10 (1-10V)	D 40WDP	110V-230V

driver remote: does not fit through cutout hole of fixture

For warranty use only Trizo21® supplied LED drivers as mentioned. For all specs and techs about drivers, see www.trizo21.com/drivers