



Choose beam:
M=medium 23° or
W=wide 40°

! driver remote
mounting excl.

Audy-Wall 1S Duo

500mA - **required remote mounted driver see below**

1 x LED array 4,32W (LED incl.) - 500mA - 2700K (487lm) or 3000K (517lm) - CRI >95

materials: brass, aluminium

WALL - IP50



FRAME brass



FRAME black



FRAME white



FRAME gunmetal



FRAME bronze



FRAME nickel



2700K	brass RING		ATWS 1223	ATWS 1213			
2700K	black RING	ATWS 1232					
2700K	white RING	ATWS 1231					
2700K	gunmetal RING	ATWS 1234					
2700K	bronze RING	ATWS 1237					
2700K	brass RING				ATWS 1243	ATWS 1773	
2700K	nickel RING				ATWS 1749		
2700K	gunmetal RING						ATWS 1794

3000K	brass RING		ATWS 1323	ATWS 1313			
3000K	black RING	ATWS 1332					
3000K	white RING	ATWS 1331					
3000K	gunmetal RING	ATWS 1334					
3000K	bronze RING	ATWS 1337					
3000K	brass RING				ATWS 1343	ATWS 1373	
3000K	nickel RING				ATWS 1349		
3000K	gunmetal RING						ATWS 1394

REQUIRED REMOTE MOUNTED DRIVER

DEVICE	DIM.	DRIVER	VOLT
1 x	LC (TRIAC/IGBT)	D 6WT500	230V
2 x	LC (TRIAC/IGBT)	D 10WT500	230V
1-4 x	PU (PUSH-DIM) + 1-10 (1-10V)	D 15WP	110V-230V
1-4 x	DA (DALI)	D 15WDA EU-US	110V-230V
1-12 x	PU (PUSH-DIM) + DA (DALI) + 1-10 (1-10V)	D 40WDP	110V-230V

driver remote: does not fit through cutout hole of fixture

For warranty use only Trizo21® supplied LED drivers as mentioned. For all specs and techs about drivers, see www.trizo21.com/drivers