



Audy-Wall 2S Duo

500mA - **required remote mounted driver see below**
 2 x LED array 4,32W (LED incl.) - 500mA - 2700K (2 x 487lm) or 3000K (2 x 517lm) - CRI >95
 materials: brass, aluminium
WALL - IP50



2700K	brass RING	ATWD 2223 ▲▼	ATWD 2213 ▲▼
2700K	black RING	ATWD 2232 ▲▼	
2700K	white RING	ATWD 2231 ▲▼	
2700K	gunmetal RING	ATWD 2234 ▲▼	
2700K	bronze RING	ATWD 2237 ▲▼	
2700K	brass RING		ATWD 2243 ▲▼
2700K	nickel RING		ATWD 2249 ▲▼
2700K	gunmetal RING		ATWD 2794 ▲▼

3000K	brass RING	ATWD 2323 ▲▼	ATWD 2313 ▲▼
3000K	black RING	ATWD 2332 ▲▼	
3000K	white RING	ATWD 2331 ▲▼	
3000K	gunmetal RING	ATWD 2334 ▲▼	
3000K	bronze RING	ATWD 2337 ▲▼	
3000K	brass RING		ATWD 2343 ▲▼
3000K	nickel RING		ATWD 2349 ▲▼
3000K	gunmetal RING		ATWD 2394 ▲▼

REQUIRED REMOTE MOUNTED DRIVER

DEVICE	DIM.	DRIVER	VOLT
1 x	LC (TRIAC/IGBT)	D 10WT500	230V
1-2 x	PU (PUSH-DIM) + 1-10 (1-10V)	D 15WP	110V-230V
1-2 x	DA (DALI)	D 15WDA EU-US	110V-230V
1-4 x	PU (PUSH-DIM) + DA (DALI) + 1-10 (1-10V)	D 40WDP	110V-230V

driver remote: does not fit through cutout hole of fixture

For warranty use only Trizo21® supplied LED drivers as mentioned. For all specs and techs about drivers, see www.trizo21.com/drivers