


## las.2



**Lichttechnik:**  
230V Power LED  
2700K  
L70/50.000 h

dimmbar über Phasenabschrittdimmer  
optional mit integriertem DALI-2-Phasendimmer

**Installation:**  
2x Kabeleinführung; Anschlussklemme 3x 2,5 mm²

**Material:**  
Aluminiumguss pulverbeschichtet  
+ pure white: Klarglas . deep black: rauchfarbenes Glas

Schutzart: IP65

Dieses Produkt enthält eine Lichtquelle  
der Energieeffizienzklasse G

coastal grade finish

**Lichtrichtung:**



**light technology:**  
230V Power LED  
2700K  
L70/50.000 h

dimmable via trailing edge dimmer  
with integrated DALI-2 phase dimmer as an option

**installation:**  
2x cable entry point; connection terminal 3x 2,5 mm²

**material:**  
aluminium die-casting powder-coated  
+ pure white: clear glass . deep black: smoked glass

protection class: IP65

This product contains a light source of  
energy efficiency class G

coastal grade finish

**light direction:**



**Farbe**  
colour



deep black  
RAL 9005

**Art.-Nr.**  
item no.

93155-BL  
93155-BL-DR . DALI-2 ready

**Systemleistung**  
system performance

6 W/115 lm



pure white  
RAL 9016

93155-WH  
93155-WH-DR . DALI-2 ready

6 W/250 lm

Größe in mm  
size in mm