


TRACIA S - DOUBLE EM. 24Vdc

IP65 IK07 CE   TIPOLOGIA / *TYPOLGY*

Applique

POSIZIONE INSTALLATIVA | *INSTALLATION POSITION*A parete | *Wall mounting*AMBIENTE INSTALLATIVO | *INSTALLATION LOCATION*Esterno | *Outdoor*

TRACIA S DOUBLE EM.

↓3 + 3↑W



kg 0,44

TRACIA S - DOUBLE EM. 24Vdc

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	↓3 + 3↑W
ALIMENTAZIONE POWER SUPPLY	24Vdc
ALIMENTATORE POWER SUPPLY UNIT	↓3 + 3↑W - 24Vdc Non incluso Not included
COLLEGAMENTO CONNECTION	Parallelo Parallel

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	2200K, 2700K, 3000K, 4000K, Red, Green, Blue
INDICE RESA CROMATICA CRI CRI	>80 (2200K, 2700K, 3000K, 4000K)
BINNING	3 step MacAdam 3 MacAdam steps
OTTICHE OPTICS	10°, 36°, 60°
FLUSSO REALE EMESSE - 3000K REAL OUTPUT FLUX	↓3 + 3↑W ↓178 + 178↑lm 36°
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES

PESO WEIGHT	Kg 0,44
FINITURE FINISHES	Bianco txt, Grigio txt, Nero txt, Corten, Antracite txt, Sand txt White, txt Grey, txt Black, Corten, txt Anthracite, Sand
INSTALLAZIONE INSTALLATION	A parete con basetta di fissaggio (inclusa) e viti (non incluse) On wall with mounting base (included) and screws (not included)
MATERIALE MATERIAL	Corpo in acciaio anticorrosione, lente in PMMA e vetro Anticorrosion aluminium body, PMMA lens and glass

CARATTERISTICHE GENERALI | GENERAL FEATURES

TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP65
GRADO DI RESISTENZA IMPACT RESISTANCE	IK07
GLOW WIRE TEST GLOW WIRE TEST	960°C
TEMPERATURA SCHERMO SCREEN TEMPERATURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	III
CALPESTABILE WALKOVER	No
CARRABILE DRIVE OVER	No
SICUREZZA STANDARD STANDARD SAFETY	/
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1

TRACIA S - DOUBLE EM. 24Vdc

ACCESSORI | ACCESSORIES

CODICE / CODE	BA001
TIPOLOGIA / TYPOLOGY	Distanziale <i>Spacer</i>  kg 0,06
MATERIALE / MATERIAL	Alluminio <i>Aluminium</i>

