

SURF 5 TUNABLE WHITE LED DOWNLIGHT

PLASTER-IN | FIXED | TW 2700K-6000K

DLD/SURF5PFTW



DLD
ARCHITECTURAL



SPECIFICATION

Power:	11W (2.2W x 5)
Current:	350mA
LED lumen:	-
Delivered lumen:	447-550lm
Beam angle:	15° 30° 40°
CCT:	2700K-6000K
CRI:	90+
Adjustable tilt:	none

DIMENSIONS



Length:	180mm
Width:	74mm
Depth:	60mm
Installed dimensions:	142 x 34mm
Cutout:	153 x 46mm

TECHNICAL

Insulation:	Class I
Protection:	IP20
Operating temperature:	-20 ~ 40°C
Average failure temperature:	L70(6k) >3600 (h)

MATERIALS

Luminaire:	Steel
Reflector:	PC
Heat sink:	Extruded aluminium
Finish:	White
Baffle finish:	Black White



SURF 5 TUNABLE WHITE LED DOWNLIGHT

PLASTER-IN | FIXED | TW 2700K-6000K

DLD/SURF5PFTW



DLD
ARCHITECTURAL

LIGHT DISTRIBUTION

Beam angle: 15°

Adjustable

UGR <10





H(m)	D(m)	E(lx)
15°		
1.0	0.27	6201
2.0	0.55	1550
3.0	0.82	689
4.0	1.10	387
5.0	1.37	248

Beam angle: 30°

Adjustable

UGR <10





H(m)	D(m)	E(lx)
30°		
1.0	0.50	2851
2.0	0.99	712
3.0	1.49	316
4.0	1.99	178
5.0	2.48	114


Beam angle: 40°

Adjustable

UGR <10



H(m)	D(m)	E(lx)
40°		
1.0	0.74	1604
2.0	1.48	401
3.0	2.21	178
4.0	2.95	100
5.0	3.69	64



01189 889414



sales@darklightdesign.com



darklightdesign.com

Darklight Design
Unit 10 Brookside Business Centre
Church Road
Swallowfield
Reading
Berkshire
RG7 1TH