


DAGO 2

design: Roberto Mantovani



Supply current

Alimentazione
Courant d'alimentation
Stromversorgung
Corriente de alimentación

350-500 mA (V_f 2,9V)

Power

Potenza
Puissance
Bestuekung
Potencia


1-2 W

Series wiring

Cablaggio in serie
Câblage en série
Verkabelung in Serie
Cableado en serie



Photometric diagrams



CCT/CRI/Flux

	350mA	500mA
2700K	89 lm	128 lm
3000K	93 lm	133 lm
4200K	103 lm	154 lm
6000K	114 lm	165 lm

Code Construction

Costruzione del codice - Construction du code produit

Bau der Produkt-Code - Construcción del código de producto

DG2 X 2 X

Color Temperature

Temperatura colore
Température couleur
Temperaturabhängige Farbe
Temperatura de color

0	1	2	3	6	7	8
2700K	3000K	4200K	6000K	Blue Blu Bleu Blau Azul	Green Verde Vert Grün	Red Rosso Rouge Rot Rojo

Finishing

Finitura
Finitions
Oberflächenfinish
Acabados

1	2	5
White Bianco Blanc Weiß Blanco	Grey Grigio Gris Grau	Black Nero Noir Schwarz Negro


Optionals

Accessori - Accessoires
Zubehör - Accesorios

CS1007

Recessing box

Controcassa
Boîtier d'encastrement
Eingießgehäuse
Caja de empotrar



Drivers

Alimentatori - Alimentateurs

Netzteile - Alimentadores

on/off	dimmable	on/off	dimmable
350 mA		500 mA	
AL1034 (1..11) 30mm IP20	AL4000 (1..12) 72mm IP20 PUSH 1..10V	AL1074 (1..7) 30mm IP20	AL4010 (1..12) 72mm IP20 PUSH 1..10V
AL1035 (1..11) 40mm IP20	AL4051 (1..12) 72mm IP20 DALI	AL1077 (1..6) 40mm IP20	AL4151 (1..12) 72mm IP20 DALI
AL1037 (1..16) 55mm IP20 S.P.	AL4053 (1..12) 60mm IP20 IGBT-TRIAC	AL1084 (1..11) 55mm IP20 S.P.	AL4153 (1..12) 60mm IP20 IGBT-TRIAC
AL9011 (1..12) 60mm IP67		AL9051 (1..10) 60mm IP67	