


DAGO 6

design: Roberto Mantovani



Supply current

Alimentazione
Courant d'alimentation
Stromversorgung
Corriente de alimentación

350-500 mA (V_f 8,7V)

Power

Potenza
Puissance
Bestuekung
Potencia


3-6 W

Series wiring

Cablaggio in serie
Câblage en série
Verkabelung in Serie
Cableado en serie



Photometric diagrams



CCT/CRI/Flux

	350mA	500mA
2700K	267 lm	384 lm
3000K	279 lm	400 lm
4200K	309 lm	462 lm
6000K	342 lm	495 lm

Code Construction

Costruzione del codice - Construction du code produit

Bau der Produkt-Code - Construcción del código de producto

DG6 X 2 X

Color Temperature

	0	1	2	3	6	7	8
Temperatura colore	2700K	3000K	4200K	6000K	Blue	Green	Red
Température couleur					Blu	Verte	Rosso
Temperaturabhängige Farbe					Bleu	Vert	Rouge
Temperatura de color					Blau	Grün	Rot
					Azul		Rojo

Finishing

	1	2	5
Finitura	White	Grey	Black
Finitions	Bianco	Grigio	Nero
Oberflächenfinish	Blanc	Gris	Noir
Acabados	Weiß	Grau	Schwarz
	Blanco		Negro


Optionals

Accessori - Accessoires
Zubehör - Accesorios

CS1007

Recessing box

Controcassa
Boîtier d'encastrement
Eingießgehäuse
Caja de empotrar



Drivers

Alimentatori - Alimentateurs

Netzteile - Alimentadores

350 mA		500 mA	
on/off	dimmable	on/off	dimmable
AL1034 (1..3)  30mm IP20	AL4000 (1..4)  72mm IP20 PUSH 1..10V	AL1074 (1..2)  30mm IP20	AL4010 (1..4)  72mm IP20 PUSH 1..10V
AL1035 (1..3)  40mm IP20	AL4051 (1..4)  72mm IP20 DALI	AL1077 (1..2)  40mm IP20	AL4151 (1..4)  72mm IP20 DALI
AL1037 (1..5)  55mm IP20 S.P.	AL4053 (1..4)  60mm IP20 IGBT-TRIAC	AL1084 (1..3)  55mm IP20 S.P.	AL4153 (1..4)  60mm IP20 IGBT-TRIAC
AL9011 (1..4)  60mm IP67		AL9051 (1..3)  60mm IP67	