


Connecting the Terminal Block

Connect main supply (**brown** - Live, **blue** - Neutral) into terminal block making sure all connections are tight.



INDOOR PENDANT LIGHT

25446

Please read instructions before commencing installation and retain for future reference.

SPECIFICATIONS

- **Lamp Type:** LED | 33W | 3000K | CRI 90 | Triac
- **Material:** Metal | Acrylic | Clear Glass
- **Ingress Protection:** IP20 Protection against entry of solid objects greater than 12mm in diameter.


INSTALLATION INSTRUCTIONS

! Electrical products can cause death, injury, or property damage. Maintenance and installation should only be carried out by a professional electrician.

- Switch off the main power supply.
- Install the ceiling anchors (1).
- Fix the mounting plate with M4 self-tapping screws (2).
- Pass the fixture and free hanging wire through the glass tube (3).
- Secure the glass tube to the cylinder using the decorative screws (4).
- Attach the free hanging wire as shown in the "Pendant Wires Fitting Steps" (5).
- Connect the live, neutral, ground wires, and the power cord (6).
- Ensure all connections are tight.
- Slide up and fix the decorative ceiling cover to conceal the wiring (7).
- Attach the final hanging wire following the "Pendant Wires Fitting Steps" (8).
- Restore power.

WARNING

! Make sure that the products are installed properly before connecting to electricity. Do not cover the luminaire. Do not exceed the maximum wattage rating of the lamp. If the light source is contained in this luminaire (integrated LED), it shall only be replaced by the manufacturer, his service agent, or a similarly qualified person.



LED

CRI 90

IP 20

0,5m

